

Key Features & Benefits:

- High Quality Construction:
 - Rugged fiberglass 5(VA) rated housing
 - Highest rated flame retardant: UL94
 - Marine grade stainless steel latches and 316 mounting brackets come standard
 - Ideal for food and beverage processing facilities and other sanitary environments
- Lens:
 - Clear 100% impact modified acrylic
 - UV stabilized lens
 - Clear polycarbonate clips
- Built For Durability:
 - Rated UL wet location: IP67 high pressure washdown up to 1500PSI, NEMA 4X housing
 - High-Temperature silicon perimeter gasket
 - Suitable for corrosive environments
- Control Options:
 - Occupancy
- 1/2" NPT / M20 fittings on both sides



Project: _____

Date: _____

Catalog #: _____

Notes: _____



Electrical Data:


Light Specifications:

Lumen Output: Up to 2,280 Lumens
 Efficacy (lm/W): Up to 114 Lumens per Watt
 Kelvin: 3500K, 4000K, 5000K
 Color Rendering Index (CRI): >82
 Rated Life: > 50,000 hrs

Driver Data:

Input Voltage: 120-277 VAC
 Input Power: 20W
 Input Current @ 120V: 0.167 Amps
 Input Current @ 240V: 0.083 Amps
 Input Current @ 277V: 0.072 Amps
 Total Harmonic Distortion (THD): <10%
 Power Factor: >0.99
 Operating Temperature: -4 ~ 122°F

Dual Tube Normal Distribution



Catalog Data:

ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	KELVIN
ESL-ID-VP2N-S-20W-F35	20W	2,260	113	3500K
ESL-ID-VP2N-S-20W-F40	20W	2,260	113	4000K
ESL-ID-VP2N-S-20W-F50	20W	2,280	114	5000K

Ordering Guide:

ESL	-	ID	-	VP2N	-	S	-	20W	-	F	-	
ESL		TYPE		SERIES		CLASS		WATTS		LENS		KELVIN
		ID Series		VP2N (Normal)		S		20W (20 Watts)		F (Frosted)		35 (3500 Kelvin) 40 (4000 Kelvin) 50 (5000 Kelvin)
												OPTIONS

Example Part Number: ESL-ID-VP2N-S-20W-F35

Options (Add as Suffix):

ESL-4OCC-LDD
ESL-REM-100

Photocell/Occupancy Sensor for Standard Mounting, Dip Switch, 0-10v
Remote for 2OCC-HDD, 3OCC/B, 4OCC-LDD, 8OCC

Dimensions:

