

**Key Features & Benefits:**

- Housing:
  - 5VA UV protected fiberglass housing
  - Silicone perimeter gasket
  - Stainless steel mounting brackets
- Lens:
  - Clear 100% impact modified acrylic
  - UV stabilized lens
  - Clear polycarbonate clips
- Gear Trey:
  - Pre-painted cold rolled steel
  - Easy access for quick installation
  - Secured with stainless steel wire
- Long Life:
  - 10 year warranty (12 hour run times)
  - 7 year warranty (24 hour run times)
- Ingress IP66 - Suitable for Wet Locations
- Control Options:
  - Photocell
  - Occupancy
- Emergency Capable
- 1/2" NPT / M20 Fittings on Both Sides

Project: \_\_\_\_\_

Date: \_\_\_\_\_

Catalog #: \_\_\_\_\_

Notes: \_\_\_\_\_



**Electrical Data:**


**Light Specifications:**

- Lumen Output: Up to 5,544 Lumens
- Efficacy (lm/W): Up to 126 Lumens per Watt
- Kelvin: 3000K, 3500K, 4000K, 5000K
- Color Rendering Index (CRI): >82
- Rated Life: > 80,000 hrs

**Driver Data:**

- Input Voltage: 120-277 VAC
- Input Power: 44W
- Input Current @ 120V: 0.367 Amps
- Input Current @ 240V: 0.183 Amps
- Input Current @ 277V: 0.158 Amps
- Total Harmonic Distortion (THD): <10%
- Power Factor: >0.99
- Operating Temperature: -4 ~ 122°F

**Single Ti  
Normal Distribution**



**Catalog Data:**

	ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	KELVIN
<b>NORMAL DISTRIBUTION</b>	ESL-TI-VP8N-S-44W-F30	44W	5,280	120	3000K
	ESL-TI-VP8N-S-44W-F35	44W	5,280	120	3500K
	ESL-TI-VP8N-S-44W-F40	44W	5,412	123	4000K
	ESL-TI-VP8N-S-44W-F50	44W	5,544	126	5000K

**Ordering Guide:** Example Part Number: **ESL-Ti-VP8N-S-44W-F40**



**Additional Options:**

- ESL-4OCC-LDD      Photocell/Occupancy Sensor for Standard Mounting, Dip Switch, 0-10v
  - ESL-REM-100      Remote for 2OCC-HDD, 3OCC/B, 4OCC-LDD, 8OCC
  - ESL-EMG-FDC-30W      Emergency Backup, 1100 Lumens, 90 Min
  - ESL-EMG-2DC-9W      Emergency Backup, DC, 9 Watts
  - ESL-CS3W-6\*      Cord Set, White, 3 wire, 6 foot
  - ESL-CS3W-6P\*      Cord Set, White, 3 wire, 6 foot, Standard Plug
  - ESL-CS3W-6TL\*      Cord Set, White, 3 wire, 6 foot, Twist lock Plug
  - ESL-CS3W-12\*      Cord Set, White, 3 wire, 12 foot
  - ESL-CS3W-12P\*      Cord Set, White, 3 wire, 12 foot, Standard Plug
  - ESL-CS3W-12TL\*      Cord Set, White, 3 wire, 12 foot, Twist lock Plug
  - ESL-SPD-277-1      Surge Protector; (100-277 VAC)
  - ESL-480V-SD01      480 Volt Step Down Transformer
  - ESL-VP-CM-VP4X      Direct Mount to the Ceiling for the 2',4',8' Narrow and Wide Body Fixture - 2 per
  - ESL-VP-45DM-VP4X      45 Degree Mount for the 2',4',8' Narrow and Wide Body Fixture - 2 per
  - ESL-VPSS      Stainless Steel Latches (2'=6 latches) (4' =8 latches) (VPHB' =12 latches)
- \*Other lengths and black cord available upon request

**Dimensions:**

