

### Key Features & Benefits:

- Extremely Quick installation
  - No Rewiring Necessary
  - No Tombstones
  - Quick Connect Technology
- Available in 2', 4' and 8' Lengths
  - 88 Available Configurations
  - 3000K, 3500K, 4000K, and 5000K Available in Ti Series
  - 4000K and 5000K available in TiHO Series

Project: \_\_\_\_\_ Date: \_\_\_\_\_

Catalog #: \_\_\_\_\_

Notes: \_\_\_\_\_



### Technical Data:

#### Light Specifications:

Total Kit Lumens: Up to 1,766 Lumens  
 Efficacy (lm/W): Up to 146 Lumens per Watt  
 Kelvin: 3000K, 3500K, 4000K, 5000K  
 Color Rendering Index (CRI): >82  
 Rated Life: > 80,000 hrs

#### Driver Data:

Input Voltage: 120-277 VAC  
 Driver Output: Single Output  
 Output Power: 13 Watts  
 Input Current @ 120V: 0.108 Amps  
 Input Current @ 240V: 0.054 Amps  
 Input Current @ 277V: 0.047 Amps  
 Total Harmonic Distortion (THD): < 10%  
 Operating Temperature: -4 ~ 122°F

### Catalog Data:

ITEM#	WATTS	TOTAL KIT LUMENS	EFFICACY (lm/W)	KELVIN	DLC QPL CODE
ESL-Ti-4SRK-S-13W-1L-F30	13W	1,722	143	3000K	PSWQD1Q7
ESL-Ti-4SRK-S-13W-1L-F35	13W	1,733	144	3500K	P840K37N
ESL-Ti-4SRK-S-13W-1L-F40	13W	1,744	144	4000K	PBW1ASAK
ESL-Ti-4SRK-S-13W-1L-F50	13W	1,766	146	5000K	PHBMXFSU

\* Made in the USA option available upon request  
 Not All Part Numbers DLC Qualified. For a Complete Listing Please Consult the DLC Qualified Products List (QPL).

### Ordering Guide:

<b>ESL</b>	-	<b>Ti</b>	-	<b>4SRK</b>	-	<b>S</b>	-	<b>13W</b>	-	<b>1L</b>	-	<b>F</b>	-		-	
ESL		TYPE		SERIES		CLASS		WATTS		Ti		LENS		KELVIN		OPTIONS
		Ti Series		4SRK (4' Strip Retrofit)		S		13W (13 Watts) 15W (15 Watts) 18W (18 Watts) 22W (22 Watts)		1L (One Ti)		F (Frosted)		30 (3000 Kelvin) 35 (3500 Kelvin) 40 (4000 Kelvin) 50 (5000 Kelvin)		

### Alternate 4' Ti Strip Kit Options:



2L Output

### What's Included:

- (1) LED Ti Bar
- (1) LED Driver
- (2) Ti Clips
- (1) Strip Retrofit Plate
- (1) UL1598C Certification Label

### Options (Add as Suffix):

ESL-EMG-2DC-9W  
ESL-4OCC-LDD  
ESL-REM-100

Emergency Back Up, DC, 9 Watt, External Battery  
Photocell/Occupancy Sensor for Standard Mounting, Dip Switch, 0-10v  
Hand Held Remote to Program 2OCC-HDD, 3OCC, 4OCC-LDD and 8OCC

### Dimensions:

