

Key Features & Benefits:

- Glass-Free, Vibration and Impact Resistant
- Optical Grade Polycarbonate Lens Tubes:
 - UV protected
 - Fire retardant
 - Corrosion resistant
- Ideal for Stairwells
- Zero Maintenance
- Die-Formed Heavy Gauge Steel
- Long Life:
 - 10 year warranty (12 hour run times)
 - 7 year warranty (24 hour run times)
- Safe - No Glass to Shatter
- Tamper Resistant Occupancy Sensor

Project: _____

Date: _____

Catalog #: _____

Notes: _____



Light Specifications:

Lumen Output: Up to 3,570 Lumens
 Efficacy (lm/W): Up to 119 Lumens per Watt
 Kelvin: 4000K, 5000K
 Color Rendering Index (CRI): >82
 Rated Life: >80,000 Hours

Driver Data:

Input Voltage: 120-277 VAC
 Input Power: 30W
 Dimming: 0-10v
 Input Current @ 120V: 0.28 Amps
 Input Current @ 240V: 0.14 Amps
 Input Current @ 277V: 0.121 Amps
 THD: <10%
 Power Factor: >0.99
 Operating Temperature: -4 ~ 122°F

Catalog Data:

ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	KELVIN	DLC QPL CODE
ESL-TiHO-F304-S-30W-F40	30W	3,330	111	4000K	PSMKMWZR
ESL-TiHO-F304-S-30W-F50	30W	3,570	119	5000K	P6XIPJLX

Ordering Guide:

ESL	-	TiHO	-	F304	-	S	-	30W	-	F	-		-	
ESL		TYPE		SERIES		CLASS		WATTS		LENS		KELVIN		OPTIONS
		TiHO Series		F304		S		30W (30 Watts)		F (Frosted)		40 (4000 Kelvin) 50 (5000 Kelvin)		

Example Part Number: ESL-TiHO-F304-S-30W-F40

Options (Add as Suffix):

ESL-4OCC-LDD	Photocell/Occupancy Sensor for Standard Mounting, Dip Switch, 0-10v
ESL-REM-100	Hand Held Remote to Program 2OCC-HDD, 3OCC, 4OCC-LDD and 8OCC
ESL-CS3W-6P	Cord Set, White, 3 wire, 6 foot, Standard Plug
ESL-CS3W-6TL	Cord Set, White, 3 wire, 6 foot, Twist lock Plug
ESL-CS3W-12P	Cord Set, White, 3 wire, 12 foot, Standard Plug
ESL-CS3W-12TL	Cord Set, White, 3 wire, 12 foot, Twist lock Plug
ESL-WP3-6	Whip, 3 wire, 6 foot
ESL-WP3-12	Whip, 3 wire, 12 foot
ESL-WBS-HH01	Hooker Hanger Mount
ESL-WBS-PM01	Pendant Mounting
ESL-SPD-277-1	Surge Protector; (100-277 VAC)
ESL-480V-SD01	Hard Sire Surge Protector; (100-277 VAC) Max Discharge Current: 20kA

Dimensions:

