

### Key Features & Benefits:

- Housing:
  - Strip fixture dimensions (48" x 4.25" x 3.75")
  - Die-formed and embossed code 22 gauge steel
  - Finish is high reflectance baked white enamel
- Gear Trey:
  - Flat heavy gauge die-formed code grade steel for all components
  - Ti mounting for 1 and 2 Ti bar locations
  - Easy Access for quick installation
- Long Life:
  - 10 year warranty (12 hour run times)
  - 7 year warranty (24 hour run times)
- 1-10v Dimming Available in Specific Models
- Control Options:
  - Photocell
  - Occupancy
- Emergency Capable
- 3/4" Knockouts on Both Ends



Project: \_\_\_\_\_

Date: \_\_\_\_\_

Catalog #: \_\_\_\_\_

Notes: \_\_\_\_\_



### Electrical Data:

#### Light Specifications:

Lumen Output: Up to 1,818 Lumens  
 Efficacy (lm/W): Up to 146 Lumens per Watt  
 Kelvin: 3000K, 3500K, 4000K, 5000K  
 Color Rendering Index (CRI): >82  
 Rated Life: > 80,000 hrs

#### Driver Data:

Input Voltage: 120-277 VAC  
 Input Power: 13W  
 Input Current @ 120V: 0.108 Amps  
 Input Current @ 240V: 0.054 Amps  
 Input Current @ 277V: 0.047 Amps  
 Total Harmonic Distortion (THD): <10%  
 Power Factor: >0.99  
 Operating Temperature: -4 ~ 122°F

### Catalog Data:

ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	KELVIN	DLC QPL CODE
ESL-Ti-WBS4-S-13W-F30	13W	1,711	142	3000K	PL8UYKC5
ESL-Ti-WBS4-S-13W-F35	13W	1,737	142	3500K	PY3QMFOO
ESL-Ti-WBS4-S-13W-F40	13W	1,764	145	4000K	PA6EX91D
ESL-Ti-WBS4-S-13W-F50	13W	1,818	146	5000K	PG60T8NW

\* Made in the USA option available upon request

Not All Part Numbers DLC Qualified. For a Complete Listing Please Consult the DLC Qualified Products List (QPL).

### Ordering Guide:

<b>ESL</b>	-	<b>Ti</b>	-	<b>WBS4</b>	-	<b>S</b>	-	<b>13W</b>	-	<b>F</b>	-		-	
ESL		TYPE		SERIES		LISTING		WATTS		LENS		KELVIN		OPTIONS
		Ti Series		WBS4		S		13W (13 Watts) 15W (15 Watts) 18W (18 Watts) 22W (22 Watts)		F (Frosted)		30 (3000 Kelvin) 35 (3500 Kelvin) 40 (4000 Kelvin) 50 (5000 Kelvin)		

Example Part Number: ESL-Ti-WBS4-S-13W-F30

### Options (Add as Suffix):

- **Emergency:**
  - ESL-EMG-2DC-9W (Emergency Backup, 1100 Lumens, 90 Minutes, Factory Installed)
- **Sensors:**
  - ESL-4OCC-LDD (Occupancy and Photocell Sensor, 0-10v Dimming, 8'-20' Mounting)
- **Miscellaneous:**
  - ESL-REM-100 (Hand Held Remote for ESL-4OCC-LDD)

### Dimensions:

