

### Key Features & Benefits:

- Glass Free
- Vibration and Impact Resistant
- Optical Grade Polycarbonate Lens Tubes:
  - UV protected
  - Fire retardant
  - Corrosion resistant
- Damp Rated
- Zero Maintenance
- Superior Heat Management
- Die-formed Heavy Gauge Steel

Project: \_\_\_\_\_

Date: \_\_\_\_\_

Catalog #: \_\_\_\_\_

Notes: \_\_\_\_\_



### Electrical Data:

#### Light Specifications:

Lumen Output: Up to 3,720 Lumens  
 Efficacy (lm/W): Up to 155 Lumens per Watt  
 Kelvin: 3500K, 4000K, 5000K  
 Color Rendering Index (CRI): >82  
 Rated Life: >50,000 Hours  
 Dimensions (LxWxH): 48.25" x 4.37" x 4.37"

#### Driver Data:

Input Voltage: 120-277 VAC  
 Input Power: 24W  
 Input Current @ 120V: 0.2 Amps  
 Input Current @ 240V: 0.1 Amps  
 Input Current @ 277V: 0.087 Amps  
 Total Harmonic Distortion (THD): <10%  
 Power Factor: >0.99  
 Operating Temperature: -4 ~ 122°F

### Catalog Data:

ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	KELVIN
ESL-ID-F313-S-24W-F35	24W	3,672	153	3500K
ESL-ID-F313-S-24W-F40	24W	3,672	153	4000K
ESL-ID-F313-S-24W-F50	24W	3,720	155	5000K

### Ordering Guide:

<b>ESL</b>	-	<b>ID</b>	-	<b>F313</b>	-	<b>S</b>	-	<b>24W</b>	-	<b>F</b>	-		-	
ESL		TYPE		SERIES		CLASS		WATTS		LENS		KELVIN		OPTIONS
		ID Series		F313		S		24W (24 Watts)		F (Frosted)		35 (3500 Kelvin) 40 (4000 Kelvin) 50 (5000 Kelvin)		

### Options (Add as Suffix):

ESL-4OCC-LDD  
ESL-REM-100

Photocell/Occupancy Sensor for Standard Mounting, Dip Switch, 0-10v  
Hand Held Remote to Program 2OCC-HDD, 3OCC, 4OCC-LDD and 8OCC

### Dimensions:

