

### Key Features & Benefits:

- Glass-Free, Vibration and Impact Resistant
- Optical Grade Polycarbonate Lens Tubes:
  - UV protected
  - Fire retardant
  - Corrosion resistant
- Ideal for Stairwells
- Zero Maintenance
- Die-Formed Heavy Gauge Steel
- Safe - No Glass to Shatter

Project: \_\_\_\_\_

Date: \_\_\_\_\_

Catalog #: \_\_\_\_\_

Notes: \_\_\_\_\_



### Electrical Data:

#### Light Specifications:

Lumen Output: Up to 5,508 Lumens  
 Efficacy (lm/W): Up to 153 Lumens per Watt  
 Kelvin: 3500K, 4000K, 5000K  
 Color Rendering Index (CRI): >82  
 Rated Life: >50,000 Hours  
 Dimensions (LxWxH): 48.25" x 4.37" x 4.37"

#### Driver Data:

Input Voltage: 120-277 VAC  
 Input Power: 36W  
 Input Current @ 120V: 0.3 Amps  
 Input Current @ 240V: 0.15 Amps  
 Input Current @ 277V: 0.13 Amps  
 Total Harmonic Distortion (THD): <10%  
 Power Factor: >0.99  
 Operating Temperature: -4 ~ 122°F

### Catalog Data:

ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	KELVIN
ESL-ID-F314-S-36W-F35	36W	5,508	153	3500K
ESL-ID-F314-S-36W-F40	36W	5,436	151	4000K
ESL-ID-F314-S-36W-F50	36W	5,508	153	5000K

**Ordering Guide:**

<b>ESL</b>	<b>ID</b>	<b>F314</b>	<b>S</b>	<b>36W</b>	<b>F</b>		
ESL	TYPE	SERIES	CLASS	WATTS	LENS	KELVIN	OPTIONS
	ID Series	F314	S	36W (36 Watts)	F (Frosted)	35 (3500 Kelvin) 40 (4000 Kelvin) 50 (5000 Kelvin)	

**Options (Add as Suffix):**

ESL-4OCC-LDD  
ESL-REM-100

Photocell/Occupancy Sensor for Standard Mounting, Dip Switch, 0-10v  
Hand Held Remote to Program 2OCC-HDD, 3OCC, 4OCC-LDD and 8OCC

**Dimensions:**

