

Key Features & Benefits:

- Housing:
 - Strip fixture dimensions (48" x 4.25" x 2")
 - Die-formed and embossed code 22 gauge steel
 - Finish is high reflectance baked white enamel
- Gear Trey:
 - Flat heavy gauge die-formed code grade steel for all components
 - Easy Access for quick installation
- 3/4" Knockouts on Both Ends

Project: _____ Date: _____
 Catalog #: _____
 Notes: _____



Electrical Data:

Light Specifications:

Lumen Output: Up to 3,720 Lumens
 Efficacy (lm/W): Up to 155 Lumens per Watt
 Kelvin: 3500K, 4000K, 5000K
 Color Rendering Index (CRI): >82
 Rated Life: >50,000 Hours
 Dimensions (LxWxH): 48.25" x 4.37" x 4.37"

Driver Data:

Input Voltage: 120-277 VAC
 Input Power: 24W
 Input Current @ 120V: 0.2 Amps
 Input Current @ 240V: 0.1 Amps
 Input Current @ 277V: 0.087 Amps
 Total Harmonic Distortion (THD): <10%
 Power Factor: >0.99
 Operating Temperature: -4 ~ 122°F

Catalog Data:

ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	KELVIN
ESL-ID-WBS4-S-24W-F35	24W	3,672	153	3500K
ESL-ID-WBS4-S-24W-F40	24W	3,672	153	4000K
ESL-ID-WBS4-S-24W-F50	24W	3,720	155	5000K

Ordering Guide:

ESL	-	ID	-	WBS4	-	S	-	24W	-	F	-		-	
ESL		TYPE		SERIES		CLASS		WATTS		LENS		KELVIN		OPTIONS
		ID Series		WBS4		S		24W (24 Watts)		F (Frosted)		35 (3500 Kelvin) 40 (4000 Kelvin) 50 (5000 Kelvin)		

Options (Add as Suffix):

ESL-4OCC-LDD
ESL-REM-100

Photocell/Occupancy Sensor for Standard Mounting, Dip Switch, 0-10v
Hand Held Remote to Program 2OCC-HDD, 3OCC, 4OCC-LDD and 8OCC

Dimensions:

