

### Key Features & Benefits:

- Housing:
  - Strip fixture dimensions (48" x 4.25" x 2")
  - Die-formed and embossed code 22 gauge steel
  - Finish is high reflectance baked white enamel
- Gear Trey:
  - Flat heavy gauge die-formed code grade steel for all components
  - Easy Access for quick installation
- 3/4" Knockouts on Both Ends

Project: \_\_\_\_\_ Date: \_\_\_\_\_

Catalog #: \_\_\_\_\_

Notes: \_\_\_\_\_



### Electrical Data:

#### Light Specifications:

Lumen Output: Up to 5,508 Lumens  
 Efficacy (lm/W): Up to 153 Lumens per Watt  
 Kelvin: 3500K, 4000K, 5000K  
 Color Rendering Index (CRI): >82  
 Rated Life: >50,000 Hours  
 Dimensions (LxWxH): 48.25" x 4.37" x 4.37"

#### Driver Data:

Input Voltage: 120-277 VAC  
 Input Power: 36W  
 Input Current @ 120V: 0.3 Amps  
 Input Current @ 240V: 0.15 Amps  
 Input Current @ 277V: 0.13 Amps  
 Total Harmonic Distortion (THD): <10%  
 Power Factor: >0.99  
 Operating Temperature: -4 ~ 122°F

### Catalog Data:

ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	KELVIN
ESL-ID-F414-S-36W-F35	36W	5,508	153	3500K
ESL-ID-F414-S-36W-F40	36W	5,436	151	4000K
ESL-ID-F414-S-36W-F50	36W	5,508	153	5000K

### Ordering Guide:

<b>ESL</b>	-	<b>ID</b>	-	<b>WBS4</b>	-	<b>S</b>	-	<b>36W</b>	-	<b>F</b>	-		-	
ESL		TYPE		SERIES		CLASS		WATTS		LENS		KELVIN		OPTIONS
		ID Series		WBS4		S		36W (36 Watts)		F (Frosted)		35 (3500 Kelvin) 40 (4000 Kelvin) 50 (5000 Kelvin)		

### Options (Add as Suffix):

ESL-4OCC-LDD  
ESL-REM-100

Photocell/Occupancy Sensor for Standard Mounting, Dip Switch, 0-10v  
Hand Held Remote to Program 2OCC-HDD, 3OCC, 4OCC-LDD and 8OCC

### Dimensions:

