

### Product Features:

- Wattage and Kelvin Selectable
- Wet Location
- 0–10V Dimming
- Robust Housing with Stainless Steel Tamper-Resistant Hardware
- Included Surface Mount Kit
- Hinged Easy-to-Install Design

Project: \_\_\_\_\_

Date: \_\_\_\_\_

Catalog #: \_\_\_\_\_

Notes: \_\_\_\_\_

### Product Specifications:

Selectable Wattage: 34W—38W—45W  
 Selectable Kelvin: 3500K—4000K—5000K  
 Lumens: Up to 7,020  
 Efficacy: Up to 130 lm/W  
 Input Voltage Options: 120–277 VAC  
 Input Frequency: 50/60 Hz  
 Operating Temperature: -4°F to 113°F (-20°C to 45°C)  
 Dimming: 0–10V Dimmable  
 CRI: >80  
 Beam Angle: 110°  
 Warranty: 5 Years  
 L70 Lifetime 100,000 hrs Calculated per TM21  
 Dimensions: 5.1" x 49.8" x 3.6"  
 Weight (lbs): 7.05



### Ordering Guide:

ESL	FAMILY	SIZE	SELECTABLE WATTAGE	GENERATION	SELECTABLE KELVIN	OPTIONS
ESL	NP-VP (VP) Vapor Tight	4 (4) 4 Foot	3445W (3454W) 34W—38W—45W	1 (1) 1st Generation	3550K (3550K) 3500K—4000K—5000K	

### Dimensions:

