

Key Features & Benefits:

- Extremely Quick installation
 - No Rewiring Necessary
 - No Tombstones
 - Quick Connect Technology
- Available in 2', 4' and 8' Lengths
 - 88 Available Configurations
 - 3000K, 3500K, 4000K, and 5000K Available in Ti Series
 - 4000K and 5000K available in TiHO Series

Project: _____ Date: _____

Catalog #: _____

Notes: _____



Technical Data:

Light Specifications:

Total Kit Lumens: Up to 2,084 Lumens
 Efficacy (lm/W): Up to 142 Lumens per Watt
 Kelvin: 3000K, 3500K, 4000K, 5000K
 Color Rendering Index (CRI): >82
 Rated Life: > 80,000 hrs

Driver Data:

Input Voltage: 120-277 VAC
 Driver Output: Single Output
 Output Power: 15 Watts
 Input Current @ 120V: 0.125 Amps
 Input Current @ 240V: 0.063 Amps
 Input Current @ 277V: 0.054 Amps
 Total Harmonic Distortion (THD): < 10%
 Operating Temperature: -4 ~ 122°F

Catalog Data:

| ITEM# | WATTS | TOTAL KIT LUMENS | EFFICACY (lm/W) | KELVIN | DLC QPL CODE |
|--------------------------|-------|------------------|-----------------|--------|--------------|
| ESL-Ti-4SRK-S-15W-1L-F30 | 15W | 2,052 | 140 | 3000K | P930BLLF |
| ESL-Ti-4SRK-S-15W-1L-F35 | 15W | 2,055 | 140 | 3500K | PT1GXH0H |
| ESL-Ti-4SRK-S-15W-1L-F40 | 15W | 2,068 | 141 | 4000K | PZ2663AZ |
| ESL-Ti-4SRK-S-15W-1L-F50 | 15W | 2,084 | 142 | 5000K | P8ZYZWN2 |

* Made in the USA option available upon request
 Not All Part Numbers DLC Qualified. For a Complete Listing Please Consult the DLC Qualified Products List (QPL).

Ordering Guide:

| | | | | | | | | | | | | | | | | |
|------------|---|-----------|---|--------------------------|---|----------|---|--|---|-------------|---|-------------|---|--|---|---------|
| ESL | - | Ti | - | 4SRK | - | S | - | 15W | - | 1L | - | F | - | | - | |
| ESL | | TYPE | | SERIES | | CLASS | | WATTS | | Ti | | LENS | | KELVIN | | OPTIONS |
| | | Ti Series | | 4SRK (4' Strip Retrofit) | | S | | 13W (13 Watts) 15W (15 Watts) 18W (18 Watts) 22W (22 Watts) | | 1L (One Ti) | | F (Frosted) | | 30 (3000 Kelvin) 35 (3500 Kelvin) 40 (4000 Kelvin) 50 (5000 Kelvin) | | |

Alternate 4' Ti Strip Kit Options:



2L Output

What's Included:

- (1) LED Ti Bar
- (1) LED Driver
- (2) Ti Clips
- (1) Strip Retrofit Plate
- (1) UL1598C Certification Label

Options (Add as Suffix):

ESL-EMG-2DC-9W
ESL-4OCC-LDD
ESL-REM-100

Emergency Back Up, DC, 9 Watt, External Battery
Photocell/Occupancy Sensor for Standard Mounting, Dip Switch, 0-10v
Hand Held Remote to Program 2OCC-HDD, 3OCC, 4OCC-LDD and 8OCC

Dimensions:

