

Key Features & Benefits:

- Extremely Quick installation
 - No Rewiring Necessary
 - No Tombstones
 - Quick Connect Technology
- Available in 2', 4' and 8' Lengths
 - 88 Available Configurations
 - 3000K, 3500K, 4000K, and 5000K Available in Ti Series
 - 4000K and 5000K available in TiHO Series

Project: _____ Date: _____

Catalog #: _____

Notes: _____



Technical Data:

Light Specifications:

Total Kit Lumens: Up to 2,915 Lumens
 Efficacy (lm/W): Up to 138 Lumens per Watt
 Kelvin: 3000K, 3500K, 4000K, 5000K
 Color Rendering Index (CRI): >82
 Rated Life: > 80,000 hrs

Driver Data:

Input Voltage: 120-277 VAC
 Driver Output: Single Output
 Output Power: 22 Watts
 Input Current @ 120V: 0.183 Amps
 Input Current @ 240V: 0.092 Amps
 Input Current @ 277V: 0.0794 Amps
 Total Harmonic Distortion (THD): < 10%
 Operating Temperature: -4 ~ 122°F

Catalog Data:

ITEM#	WATTS	TOTAL KIT LUMENS	EFFICACY (lm/W)	KELVIN	DLC QPL CODE
ESL-Ti-4SRK-S-22W-1L-F30	22W	2,853	136	3000K	P7QUMAVQ
ESL-Ti-4SRK-S-22W-1L-F35	22W	2,875	136	3500K	PQ63WGNF
ESL-Ti-4SRK-S-22W-1L-F40	22W	2,893	137	4000K	PE4548HV
ESL-Ti-4SRK-S-22W-1L-F50	22W	2,915	138	5000K	P6L4KNJ4

* Made in the USA option available upon request
 Not All Part Numbers DLC Qualified. For a Complete Listing Please Consult the DLC Qualified Products List (QPL).

Ordering Guide:

ESL	-	Ti	-	4SRK	-	S	-	22W	-	1L	-	F	-		-	
ESL		TYPE		SERIES		CLASS		WATTS		Ti		LENS		KELVIN		OPTIONS
		Ti Series		4SRK (4' Strip Retrofit)		S		13W (13 Watts) 15W (15 Watts) 18W (18 Watts) 22W (22 Watts)		1L (One Ti)		F (Frosted)		30 (3000 Kelvin) 35 (3500 Kelvin) 40 (4000 Kelvin) 50 (5000 Kelvin)		

Alternate 4' Ti Strip Kit Options:



2L Output

What's Included:

- (1) LED Ti Bar
- (1) LED Driver
- (2) Ti Clips
- (1) Strip Retrofit Plate
- (1) UL1598C Certification Label

Options (Add as Suffix):

ESL-EMG-2DC-9W
ESL-4OCC-LDD
ESL-REM-100

Emergency Back Up, DC, 9 Watt, External Battery
Photocell/Occupancy Sensor for Standard Mounting, Dip Switch, 0-10v
Hand Held Remote to Program 2OCC-HDD, 3OCC, 4OCC-LDD and 8OCC

Dimensions:

