



Exit Sign
Emergency Lighting
Red Letters
EM-ELC-R

Exit Sign
Emergency Lighting
Green Letters
EM-ELC-G

OTHER AVAILABLE MODELS



Exit Sign
Red Letters
with BBU
EM-EX-R



Exit Sign
Green Letters
with BBU
EM-EX-G

Features & Specifications

- Battery backup type: Lithium Ion • Battery operating time: >90 minutes • Recharge time: 24 hours
- Voltage: 120-277V • Emergency light CCT: 6500K • Temp rating: 32°F-104°F • L70: >50,000
- Warranty: 5 year limited



Exit Sign
Emergency Lighting
Red Letters
w/Remote Capability
EM-ELC-R-RC



Emergency Light
Single
EM-ELR-H1
Wet Rated



Emergency Light
Double
EM-ELR-H2
Wet Rated



Emergency Light
EM-EL
Emergency Light
w/Remote Capability
EM-EL-RC

PART NUMBER GUIDE



ORDERING GUIDE

Part #	Model #	Description	Replaces	LED Watts	Lumens	LPW	CCT	Product Dimensions	CRI	Input Voltage	Case Pack
EM-EX-R	55301101	Exit Sign	N/A	2.2w	N/A	0	6500K	11.6 x 7.4 x 1.7 in.	N/A	120/277V	6
EM-EX-G	55301102	Exit Sign Green Letters	N/A	2.2w	N/A	0	6500K	11.6 x 7.4 x 1.7 in.	N/A	120/277V	6
EM-ELC-R	55502101	Emergency Light/Exit Sign Combo	N/A	2.4w	263	110	6500K	19.8 x 7.9 x 4.3 in.	N/A	120/277V	6
EM-ELC-G	55502102	Emergency Light/Exit Sign Combo Green Letters	N/A	2.4w	263	110	6500K	19.8 x 7.9 x 4.3 in.	N/A	120/277V	6
EM-ELC-R-RC	55502201	Emergency Light/Exit Sign Combo W/ Remote Capability	N/A	2.4w	263	110	6500K	19.8 x 7.9 x 4.3 in.	N/A	120/277V	6
EM-EL	55501101	Emergency Light (2-head)	N/A	2.4w	249	104	6500K	13.7 x 4.1 x 3.5 in.	N/A	120/277V	6
EM-EL-RC	55501201	Emergency Light W/Remote Capability (2-head)	N/A	2.4w	249	104	6500K	13.7 x 4.1 x 3.5 in.	N/A	120/277V	6
EM-ELR-H1*	55503101	Emergency Light Fixture - Single (Wet Rated)	N/A	1.2w	131	109	6500K	4.3 x 4.3 x 6.2 in.	N/A	120/277V	12
EM-ELR-H2*	55503201	Emergency Light Fixture - Double (Wet Rated)	N/A	2.4w	263	110	6500K	4.3 x 4.3 x 6.2 in.	N/A	120/277V	12

PACKAGING SPECIFICATIONS

Part #	Model #	UPC	UCC	Inner Carton Dimensions	Inner Carton Weight	Shipper/Master Carton Dimensions	Shipper/Master Carton Weight
EM-EX-R	55301101	849489009667	50849489009662	12.2 x 8.0 x 2.4 in.	3 lbs.	15.4 x 12.8 x 8.9 in.	18 lbs.
EM-EX-G	55301102	849489009667	50849489009136	12.2 x 8.0 x 2.4 in.	3 lbs.	15.4 x 12.8 x 8.9 in.	18 lbs.
EM-ELC-R	55502101	849489009650	50849489009655	13.8 x 4.7 x 3.9 in.	4.3 lbs.	19.7 x 17.3 x 15.2 in.	25.8 lbs.
EM-ELC-G	55502102	849489009650	50849489009143	13.8 x 4.7 x 3.9 in.	4.3 lbs.	19.7 x 17.3 x 15.2 in.	25.8 lbs.
EM-ELC-R-RC	55502201	849489009681	50849489009686	13.8 x 4.7 x 3.9 in.	4.3 lbs.	19.7 x 17.3 x 15.2 in.	25.8 lbs.
EM-EL	55501101	849489009643	50849489009648	12.4 x 5.0 x 4.1 in.	1.8 lbs.	16.0 x 12.8 x 9.1 in.	11.2 lbs.
EM-EL-RC	55501201	849489009698	50849489009693	12.4 x 5.0 x 4.1 in.	1.8 lbs.	16.0 x 12.8 x 9.1 in.	11.2 lbs.
EM-ELR-H1	55503101	849489009704	50849489009709	4.7 x 4.7 x 6.7 in.	0.7 lbs.	14.8 x 9.9 x 14.2 in.	8.8 lbs.
EM-ELR-H2	55503201	849489009711	50849489009716	9.8 x 7.3 x 4.3 in.	1 lbs.	22.5 x 8.9 x 18.3 in.	15.8 lbs.