Eaton OSP10D-GY

Catalog Number: OSP10D-GY

Eaton occupancy sensor dual switch, Flush, 120/277V, Wire leads, Maint closure, Gray, Incand, MLV, ELV, Flr, halo, Elect mtr lds, 1-pole, 3-way, 1-ph, 1000 sq ft, 2-relay, 800W (Inc/hal @120V), 1200W (Flr @120V), 2200W (Flr @277V) 717543

NOM

General specifications

Product Name Catalog Number OSP10D-GY Eaton occupancy sensor dual switch

UPC Product Length/Depth

032664717543 3 in

Product Height Product Width

5.13 in 3.3 in

Product Weight Certifications

50.738 lb cULus Listed



Product specifications

Special features

Dual switch

Relay

Dual

Phase

Single-phase

Load type

ELV

FLR

Electrical motor loads

HAL

INC

MLV

Closure type

Maintained

Color

Gray

Wiring method

Wire leads

Mounting method

Flush

Range

1000 sq ft

Number Of Poles

Single-pole

Туре

Occupancy sensor dual switch

Sensor type

Occupancy

Power consumption

2200 W (FLR at 277 V) 1200 W (FLR at 120 V)

800 W (INC/HAL at 120 V)

Number of ways

Three-way

Voltage rating

Resources

Brochures

Arrow Hart commercial lighting controls brochure

Specifications and datasheets

Eaton Specification Sheet - OSP10D-GY



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2023 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia