

# Eaton TR291W

Catalog Number: TR291W

Eaton commercial grade combination switch, tamp resist, auto-grnd, Stand, #14 - #12 AWG, 20A, 20A recept, Commer, 120V switch, 125V recept, bk and sd wiring, togg, Maint closure, Screw, Brass, wht, 5-15R, -20-60C, dplx, thermoplas, PVC



## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton commercial grade combination switch	TR291W
	UPC
	032664722387
<b>Product Length/Depth</b>	<b>Product Height</b>
1.3 in	4.19 in
<b>Product Width</b>	<b>Product Weight</b>
1.08 in	0.242 lb
<b>Compliances</b>	<b>Certifications</b>
RoHS Compliant	cULus Listed

## Product specifications

### Special features

Tamper resistant, auto-ground

### Connector type

Screw

### Switch type

Single-pole

### Configuration

Toggle switch

Receptacle

### Closure type

Maintained

### Color

White

### Wiring method

Back and side

### Material

PVC

Thermoplastic

### Mounting method

Flush

### Allowable wire size

#14-12 AWG

### Amperage Rating

20 A switch, 20 A receptacle

### Number Of Poles

Single-pole

### Contact type

Brass

### Type

Standard

### NEMA configuration

5-15R

### Device grade

Commercial

### Style type

## Resources

### Specifications and datasheets

[Eaton Specification Sheet - TR291W](#)

[Combination devices instruction sheet](#)

Duplex

NEMA Rating

5-20R

5-15R

Operating temperature

-20 to 60 °C

Voltage rating

120V switch, 125V receptacle

Application

Commercial

Torque rating

12-14 lbf-inch

Actuator

Toggle



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)