



Project	
Notes	
Type	Date
Cat. No.	



**LVTS™ Series** CCT Adjustable Vaportight LED Strip

**DESCRIPTION**

The LVTS series is a next generation LED Vapor Tight fixture that provides maximum light output with durable construction. It is ideal for featuring a one piece polycarbonate housing and lens. The LVTS was designed to meet or exceed IES recommended foot-candle levels at installed heights for parking garages. Ideal for utility lighting, parking garages and stairwells; where meeting applicable building and safety codes is required.

**Specification**



**Construction**

UV stabilized, injection molded, impact resistant, polycarbonate housing. 20 gauge steel channel cover, lens design and materials provide uniform appearance without pixelation.

**Certification**

All luminaires are built to UL 1598 and 2108 standards, and bear appropriate ETL labels. Wet location labeling is standard. Emergency equipped fixtures labeled UL924. Adheres to LM70, LM80, and TM21 industry standards. DesignLights Consortium® (DLC) DLC qualified product. Not all models of this product may be DLC qualified. Please check the DLC Qualified Products List at [www.designlights.org/QPL](http://www.designlights.org/QPL) to confirm which models are qualified.

**Warranty**

5-year Limited Warranty. See warranty documentation for more information.

**Electrical**

Equipped standard with 0-10V continuous dimming driver that works with any standard 0-10V control/dimmer. Long-Life LED's 60,000 hours at L80 with projected life over 100,000 hours for reduced life cycle maintenance costs Luminaire can be ceiling or suspend mounted. Power connection is easily accommodated through pre-drilled holes at each end, watertight plugs ship standard on each end.

**Installation**

Quick mounting clips included. Suitable for suspension or surface mounting.

**Options**

Optional On/Off Motion Sensor, high voltage transformer, emergency battery backups, whips and cords.

**LVTS Series**

- 48" Housing**  
34W (4,420 Lumens)  
45W (5,850 Lumens)
- 96" Housing**  
55W (7,150 Lumens)

Rated Life 60,000 hours  
Limited Warranty 5 years  
Efficacy 114 lm/W  
Continuous Dimming



**Quick Ship**  
\*Available first quarter of 2020

LVTS-34-MVD-830/40/50  
LVTS-45-MVD-830/40/50

**Ordering Information**

Example: LVTS-45-MVD-830/40/50-OS

LVTS	45	MVD	8	30/40/50
<b>Series</b> LVTS CCT Adjustable Vaportight LED Strip	<b>Rated Wattage</b> <b>48" Housing</b> 34- 34W (4,420 Lumens) <sup>2</sup> 45- 45W (5,850 Lumens) <sup>2</sup> <b>96" Housing</b> 8-55- 55W (7,150 Lumens) <sup>2</sup>	<b>Driver Type</b> MV- 120-277V <sup>1</sup> MVD- 120-277V; 0-10V Dimming <sup>2</sup> HVD-347-480V,0-10V Dimming <sup>1</sup> HV-347-480V <sup>1</sup>	<b>CRI</b> 8 80+ CRI	<b>Color Temp</b> 30/40/50 3000K, 4000K 5000 K <sup>2</sup> Adjustable Switch
<b>Options</b>				
		<b>Emergency Backup</b> EML8 800lm EML16 1600lm	<b>Controls</b> OS- Fixture Mounted Occupancy Sensor, On/Off MOS- Integral Microwave Sensor, On/Off MOSB-Integral Bi-Level Microwave Sensor MOSB-FM- Microwave Bi-Level Sensor Fixture mount	<b>Accessories</b> FW3 6' 3 Wire Fixture Whip FW4 6' 4 Wire Fixture Whip

Specifications and Dimensions subject to change without notice

## Performance Summary


Input Voltage	120-277V
Input Frequency	50/60 Hz
Rated Wattage	See Performance Table
Delivered Lumens	See Performance Table
Efficacy	> 130 lm/W
CRI	80+, R9 > 0
Available CCT <sup>1</sup>	3000K, 4000K, 5000K Adjustable
Color Consistency <sup>2</sup>	5-step MacAdam Ellipse
Rated Life	60,000 hours
L70 <sup>3</sup>	> 72,000 hours or > 45,000
Power Factor	>0.99
THD	< 2.3%
Dimming	0-10V Continuous (10-100%)
Operating Temp.	-18°C to 40°C
IP Rating	IP65 Wet Location

## Configurations

## CCT Adjustable Instructions

In order to switch Kelvin temperatures, flip the switch to the desired configuration.

## COLOR TEMPERATURE ADJUSTMENT SETTING



## Performance Data

Lens Type	Form Factor	Catalog No.	Rated Wattage (W)	Delivered Lumens	Efficacy (lm/W)
Frosted Acrylic	48"	<a href="#">LVTS-34-MVD-830/40/50</a>	34W	4,420	130
		<a href="#">LVTS-45-MVD-830/40/50</a>	45W	5,850	130
	96"	<a href="#">LVTS-8-55-MVD-830/40/50</a>	55W	7,150	130

## NOTES:


- <sup>1</sup> Made to order items. Minimum 90 day lead time. Minimum 500 order quantity.
- <sup>2</sup> DLC Listed
- <sup>3</sup> DLC Premium Listed
- <sup>4</sup> Quick ship: 5000K. Other CCTs may require a lead time or be special order
- <sup>5</sup> Typical color consistency. May vary or be changed.
- <sup>6</sup> L70 hours calculated based on LED package manufacturer LM80 report and ISTMT report of LED in luminaire. Stated values are for select catalog numbers. Contact GlobaLux for detailed information.
- <sup>7</sup> Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C.




Specifications and Dimensions subject to change without notice

Product Dimensions

LVTS-40/52 (48" housing)



LVTS-55/104 (96" housing)




CCT Adjustable Vaportight LED Strip

Photometric Data

LVTS-34-MVD-830/40/50 Tested in accordance to IESNA LM-79

Polar Candela Curve




Zonal Lumen Summary

Zonal Lumen Summary		
Zone	Lumens	% Luminaire
0-30	1,208.1	25.7%
0-40	1,961.3	41.7%
0-60	3,420.4	72.8%
60-90	1,113.6	23.7%
70-100	638.6	13.6%
90-120	145.5	3.1%
0-90	4,534.0	96.5%
90-180	166.3	3.5%
0-180	4,700.3	100%

Photometric Data

LVTS-45-MVD-830/40/50 Tested in accordance to IESNA LM-79

Polar Candela Curve



Zonal Lumen Summary

Effective Floor Cavity Reflectance: 20%

Zonal Lumen Summary		
Zone	Lumens	% Luminaire
0-30	1,535.0	26.1%
0-40	2,489.1	42.3%
0-60	4,462.2	75.9%
60-90	1,340.5	22.8%
70-100	648.6	11%
90-120	77.8	1.3%
0-90	5,802.7	98.7%
90-180	77.8	1.3%
0-180	5,880.5	100%

Accessory Options



Whips

- CH-3.5 36 in Chain Hanger Kit
- FW3 6' 3 Wire Fixture Whip with 1/2 Connector. in
- FW3-BL 6' 3 Wire Fixture Whip with 1/2 Connector (Black)
- FW3-M 6' 3 Wire Fixture Whip with 1/2 Connector (Metal)
- FW312 12' 3 Wire Fixture Whip with 1/2 Connector. in
- FW4 6' 4 Wire Flex/Whip\_
- RS Rocker Switch
- SM-22 2x2 Surface Mount Shroud Kit for RLP, LTF Seris Fixtures
- SM-24 2x4 Surface Mount Shroud Kit for RLP, LTF Series Fixtures



© 2019 GloLux Lighting, LLC. All rights reserved. For informational purposes only. Reproduction in whole or part is prohibited without prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequences of its use. GloLux Lighting reserves the rights make changes in specification at any time without notice.

**GloLux Lighting LLC**  
 www.globaluxlighting.com  
 2037 S. Vineyard Ave  
 Ontario, CA 91761  
 Ph: 909-591-7506