

MR11

FEATURES

- Suitable to replace 20W Halogen MR11 lamps
- Compatible with most low-voltage electronic transformers*
- Compact size 1:1 halogen form factor
- Flood beam angles
- Suitable for use in totally enclosed fixtures
- Suitable for use in damp location
- Fixture operating temperature: -13°F to 95°F (-25°C to 35°C) Lamp ambient temperature: -13°F to 113°F (-25°C to 45°C)
- Rated Lifetime (L70): 25,000hrs
- 3 year limited warranty**










SPE	SPECIFICATIONS														
Product	Model	Equiv.	Wattage (W)	ССТ	Lumens	Efficacy (LPW)	Input Voltage		CBCP (cd)	CRI	Dim.	Power Factor	Base	Fixture Rating	T20
35790	2.5MR11/827FL35	20W	2.5	2700K	200	80	12V	FL 35°	400	82	No	0.5	GU4	Enclosed	√
40715	3MR11/840NF30	20W	3	4000K	220	73	12V	NF 30°	620	82	No	0.9	GU4	Enclosed	N.A.

^{*}This lamp might not be compatible with all low-voltage transformers. Please visit www.greencreative.com for compatibility information. **Please visit www.greencreative.com for Limited Warranty terms.

DIMENSIONS & WEIGHT






Model	Base	MOL	Dia.	Weight
2.5MR11/827FL35	GU4	1-1/2"	1-3/8"	0.04lb
3MR11/840NF30	GU4	1-1/2"	1-3/8"	0.07lb


ORDERING INFORMATION								
Product Series		Master Carton		Shipping Carton				
Product Series	Case QTY	Case Dimensions (LxWxH)	Case Weight	Case QTY	Case Dimensions (LxWxH)	Case Weight		
MR11 2.5W	12PCS	4-11/16" x 3-1/8" x 4-3/8"	0.75 lb	48PCS	10-1/4" x 7-3/16" x 5-5/16"	3.17 lb		
MR11 3W	12PCS	5-7/8 x 3"-15/16" x 4-5/16"	1.16 lb	48PCS	12-3/8" x 8-5/8" x 5-5/16"	5.11 lb		

ILLUMINANCE & CANDELA DISTRIBUTION

2.5MR11/827FL35




Diameter	Footcandles
1.6	171
3.2	43
4.8	19
6.4	11
8.0	7




Degree	Candela	
0	432	
5	392	
15	226	
25	109	
35	58	
45	27	

3MR11/840NF30



Diameter	Footcandles
1.6	69
3.2	17
4.8	8
6.4	4
8.0	3



Degree	Candela
0	620
5	583
15	326
25	102
35	26
45	9

Note: All rights reserved. All sizes and specifications are subject to change at any time without notice.