



### 3 Level power output



Power select switch allows light output to be tailored to application requirements and can be adjusted from high to low.



- Integral driver suitable for 120-277V
- E26 version is dimmable at 120V line voltage
- EX39 version has integrated side switch for field selectable lumen output
- Suitable for use in totally enclosed fixtures
- Integral 6kV surge protector

- Compatible with magnetic ballasts - DIRect installation
- Built-in universal voltage driver - BYPass installation
- Omni directional light distribution suitable for horizontal or vertical installations
- Replaces G24q & GX24q (4-pin) or G24d & GX24d (2-pin) 13W-26W CFL lamps

### SPECIFICATIONS

| Product | Model         | CCT   | Lumens | CRI (typ.) | LPW | Dim | Equiv. | Beam Angle | Life (hrs) | Voltage  | Encl. |
|---------|---------------|-------|--------|------------|-----|-----|--------|------------|------------|----------|-------|
| 34996   | 7PLO/827/HYBM | 2700K | 770    | 82         | 110 | No  | 13-18W | 360°       | 50,000     | 120-277V | Yes   |
| 34997   | 7PLO/830/HYBM | 3000K | 790    | 82         | 112 | No  | 13-18W | 360°       | 50,000     | 120-277V | Yes   |
| 34998   | 7PLO/835/HYBM | 3500K | 820    | 82         | 117 | No  | 13-18W | 360°       | 50,000     | 120-277V | Yes   |
| 34999   | 7PLO/840/HYBM | 4000K | 850    | 82         | 121 | No  | 13-18W | 360°       | 50,000     | 120-277V | Yes   |
| 35000   | 9PLO/827/HYBM | 2700K | 1,100  | 82         | 122 | No  | 26W    | 360°       | 50,000     | 120-277V | Yes   |
| 35001   | 9PLO/830/HYBM | 3000K | 1,150  | 82         | 125 | No  | 26W    | 360°       | 50,000     | 120-277V | Yes   |
| 35002   | 9PLO/835/HYBM | 3500K | 1,200  | 82         | 130 | No  | 26W    | 360°       | 50,000     | 120-277V | Yes   |
| 35003   | 9PLO/840/HYBM | 4000K | 1,250  | 82         | 133 | No  | 26W    | 360°       | 50,000     | 120-277V | Yes   |

### SPECIFICATIONS

| Product | Model                  | CCT   | Lumens | CRI (typ.) | LPW | Dim | Equiv. | Beam Angle | Life (hrs) | Voltage  | DLC  |
|---------|------------------------|---|--------|------------|-----|-----|--------|------------|------------|----------|------|
| 36165   | 17A21/830/277V/DIM     | 3000K   | 2,000  | 82         | 118 | Yes | 125W   | 230°       | 50,000     | 120-277V | N.A. |
| 36166   | 17A21/835/277V/DIM     | 3500K   | 2,000  | 82         | 118 | Yes | 125W   | 230°       | 50,000     | 120-277V | N.A. |
| 36167   | 17A21/840/277V/DIM     | 4000K   | 2,100  | 82         | 124 | Yes | 125W   | 230°       | 50,000     | 120-277V | N.A. |
| 36168   | 17A21/850/277V/DIM     | 5000K   | 2,100  | 82         | 124 | Yes | 125W   | 230°       | 50,000     | 120-277V | N.A. |
| 36169   | 24HID/830/277V/E26/DIM | 3000K   | 3,100  | 82         | 129 | Yes | 200W   | 230°       | 50,000     | 120-277V | N.A. |
| 36214   | 24HID/835/277V/E26/DIM | 3500K   | 3,100  | 82         | 129 | Yes | 200W   | 230°       | 50,000     | 120-277V | N.A. |
| 36170   | 24HID/840/277V/E26/DIM | 4000K   | 3,200  | 82         | 133 | Yes | 200W   | 230°       | 50,000     | 120-277V | N.A. |
| 36171   | 24HID/850/277V/E26/DIM | 5000K   | 3,200  | 82         | 133 | Yes | 200W   | 230°       | 50,000     | 120-277V | N.A. |
| 36158   | 24HID/830/277V/EX39/SD | 3000K   | 3,100  | 82         | 129 | No  | 200W   | 230°       | 50,000     | 120-277V | ✓    |
| 36159   | 24HID/835/277V/EX39/SD | 3500K   | 3,100  | 82         | 129 | No  | 200W   | 230°       | 50,000     | 120-277V | ✓    |
| 36160   | 24HID/840/277V/EX39/SD | 4000K   | 3,200  | 82         | 133 | No  | 200W   | 230°       | 50,000     | 120-277V | ✓    |
| 36161   | 24HID/850/277V/EX39/SD | 5000K   | 3,200  | 82         | 133 | No  | 200W   | 230°       | 50,000     | 120-277V | ✓    |
| 36172   | 34HID/830/277V/E26/DIM | 3000K   | 4,500  | 82         | 132 | Yes | 300W   | 230°       | 50,000     | 120-277V | N.A. |
| 36173   | 34HID/840/277V/E26/DIM | 4000K   | 5,000  | 82         | 147 | Yes | 300W   | 230°       | 50,000     | 120-277V | N.A. |
| 36174   | 34HID/850/277V/E26/DIM | 5000K   | 5,000  | 82         | 147 | Yes | 300W   | 230°       | 50,000     | 120-277V | N.A. |
| 36162   | 34HID/830/277V/EX39/SD | 3000K   | 4,500  | 82         | 132 | No  | 175W   | 230°       | 50,000     | 120-277V | ✓    |
| 36163   | 34HID/840/277V/EX39/SD | 4000K   | 5,000  | 82         | 147 | No  | 175W   | 230°       | 50,000     | 120-277V | ✓    |
| 36164   | 34HID/850/277V/EX39/SD | 5000K   | 5,000  | 82         | 147 | No  | 175W   | 230°       | 50,000     | 120-277V | ✓    |
| 16325   | E26 EXTENDER           | E26 Lamp Extender Adds 1.30" (33mm) to Lamp Height  |        |            |     |     |        |            |            |          |      |
| 35050   | EX39 EXTENDER          | EX39 Lamp Extender Adds 1.70" (43mm) to Lamp Height |        |            |     |     |        |            |            |          |      |
| 97718   | 10SURGE/277V           | 10kV Surge Protector                                |        |            |     |     |        |            |            |          |      |