PLS 5.5W HYB GX23 TITANIUM LED SERIES









PRO

- HYBrid installation DIRect on BYPass
- Compatible with magnetic ballasts DIRect installation
- Built-in universal voltage driver BYPass installation
- Exceptional efficacy 91 LPW
- Lasts 5 times longer than CFL
- Suitable for use in totally enclosed fixtures Ballast Dependent. Please refer to www.greencreative.com for full ballast / dimmer compatibility list.





























COMPACT FORM FACTOR AND ROTATABLE BASE SUITABLE FOR ALL APPLICATIONS




PLS 5.5W HYB GX23 TITANIUM LED SERIES









Base: GX23 (2-pin CFL)

Voltage: Magnetic ballast compatible

120-277V

Dimmable: No PF: 0.9

Lifetime: 50,000 hrs
Weight: 0.08lb / 38g



SPECIFICATIONS

Model	Product	Power (W)	сст	CRI (typ.)	Lumens	LPW	Beam Angle
5.5PLS/827/HYB/GX23	57820	5.5	Soft White 2700K	80	450	82	120°
5.5PLS/830/HYB/GX23	57821	5.5	Warm White 3000K	80	500	91	120°
5.5PLS/835/HYB/GX23	57822	5.5	Neutral White 3500K	80	500	91	120°
5.5PLS/840/HYB/GX23	57823	5.5	Cool White 4000K	80	520	95	120°

Suitable for use in totally enclosed fixtures

^{**} Suitable for damp locations. Not for use where directly exposed to weather or water

^{***} Full installation guide and more details available on website