

Project Name:	Type:
Part Number:	Date:



GREENCREATIVE

HIGH CRI BR LAMP Family

FEATURES

- Suitable to replace 45W, 65W, 75W and 85W incandescent lamps
- Smooth dimming with most forward and reverse phase dimmers*
- CRI 93 produces rich and vibrant colors
- Suitable for use in totally enclosed fixtures
- Shatter resistant
- Suitable for use in damp locations
- Fixture operating temperature: -4°F to 95°F (-20°C to 35°C)
- Lamp ambient temperature: -4°F to 113°F (-20°C to 45°C)
- Rated Lifetime (L70): 25,000hrs
- 3 year limited warranty**



111021



SPECIFICATIONS

Product	Model	CCT	Lumens	Wattage (W)	Efficacy (LPW)	Power Factor	Input Voltage	Equiv.	CRI	Dim.*	Beam Angle	Fixture Rating	ES / T20
36688	7R20DIM/927	2700K	590	7	84	0.7	120V	45W	93	Yes	120°	Enclosed	√/√
36689	7R20DIM/930	3000K	590	7	84	0.7	120V	45W	93	Yes	120°	Enclosed	√/√
36690	7R20DIM/940	4000K	590	7	84	0.7	120V	45W	93	Yes	120°	Enclosed	√/√
36692	9BR30DIM/930	3000K	770	9	86	0.7	120V	65W	93	Yes	120°	Enclosed	√/√
36693	9BR30DIM/940	4000K	770	9	86	0.7	120V	65W	93	Yes	120°	Enclosed	√/√
36694	11BR30DIM/927	2700K	920	11	84	0.7	120V	65W	93	Yes	120°	Enclosed	√/√
36695	11BR30DIM/930	3000K	920	11	84	0.7	120V	65W	93	Yes	120°	Enclosed	√/√
36696	11BR30DIM/940	4000K	920	11	84	0.7	120V	65W	93	Yes	120°	Enclosed	√/√
36697	11BR40DIM/927	2700K	950	11	86	0.7	120V	75W	93	Yes	120°	Enclosed	√/√
36698	11BR40DIM/930	3000K	950	11	86	0.7	120V	75W	93	Yes	120°	Enclosed	√/√
36699	11BR40DIM/940	4000K	950	11	86	0.7	120V	75W	93	Yes	120°	Enclosed	√/√
36700	13BR40DIM/927	2700K	1,100	13	85	0.7	120V	85W	93	Yes	120°	Enclosed	√/√
36701	13BR40DIM/930	3000K	1,100	13	85	0.7	120V	85W	93	Yes	120°	Enclosed	√/√
36702	13BR40DIM/940	4000K	1,100	13	85	0.7	120V	85W	93	Yes	120°	Enclosed	√/√

* This lamp might not be compatible with all dimmers. Please visit www.greencreative.com for compatibility information.

** Please visit www.greencreative.com for Limited Warranty terms


Project Name:	Type:
Part Number:	Date:



GREENCREATIVE

HIGH CRI BR LAMP Family

DIMENSION & WEIGHT



Model	Base	MOL	Dia.	Weight
7R20DIM/xxx	E26	3-7/8"	2-1/2"	0.11 lb
9BR30DIM/xxx	E26	5"	3-3/4"	0.16 lb
11BR30DIM/xxx	E26	5"	3-3/4"	0.16 lb
11BR40DIM/xxx	E26	6-1/8"	4-7/8"	0.33 lb
13BR40DIM/xxx	E26	6-1/8"	4-7/8"	0.34 lb

ORDERING INFORMATION

Model	Shipping Carton		
	Case Qty	Case Dimensions (LxWxH)	Case Weight
7R20DIM/xxx	72 PCS	15-15/16" x 15-15/16" x 9-5/8"	14.37 lb
9BR30DIM/xxx	48 PCS	24-7/16" x 16-9/16" x 12-5/16"	12.35 lb
11BR30DIM/xxx	48 PCS	24-7/16" x 16-9/16" x 12-5/16"	12.35 lb
11BR40DIM/xxx	24 PCS	21-7/8" x 16-1/8" x 15-3/4"	11.86 lb
13BR40DIM/xxx	24 PCS	21-7/8" x 16-1/8" x 15-3/4"	12.13 lb

Where xxx means 824-965 which indicates CRI and color temperature

CERTIFICATION INFORMATION

Product	Model	ES ID#
36688	7R20DIM/927	2386744
36689	7R20DIM/930	2386745
36690	7R20DIM/940	2386746
36691	9BR30DIM/927	2388060
36692	9BR30DIM/930	2388061
36693	9BR30DIM/940	2388062
36694	11BR30DIM/927	2386735
36695	11BR30DIM/930	2386736
36696	11BR30DIM/940	2386737
36697	11BR40DIM/927	2386738
36698	11BR40DIM/930	2386739
36699	11BR40DIM/940	2386740
36700	13BR40DIM/927	2386741
36701	13BR40DIM/930	2386742
36702	13BR40DIM/940	2386743

Note: All rights reserved. All sizes and specifications are subject to change at any time without notice.