PLS V 5.5W HYB GX23 TITANIUM LED SERIES











- U HYBrid installation DIRect or BYPass
- Compatible with magnetic ballasts DIRect installation
- Built-in universal voltage driver BYPass installation
- U High efficacy 113 LPW
- Lasts 4 times longer than CFL
- Available in 2700K, 3000K, 3500K & 4000K CCT















PLS PRODUCT FEATURES

CFL Replacement - HYBrid Installation

The PLS V blends innovative design with the latest in LED technology. The GREEN CREATIVE PLS V is the only CFL GX23 base replacement designed for vertical applications. This lamp operates on existing 13W magnetic ballasts or on 120-277V line voltage.



Fully Round Design




GREEN CREATIVE PLS V LED Lamp





The PLS V lamp features a fully round design. Compared to other PLS lamps, the GREEN CREATIVE PLS V improves the overall light output and aesthetics of the fixture, especially in cans.

PLS V 5.5W HYB GX23 TITANIUM LED SERIES










GX23 (2-pin CFL) Base:

Voltage: Magnetic ballast compatible

120-277V

Dimmable: No PF: 0.9

Lifetime (L70): 50,000 hrs Weight: 0.16lb / 73g



SPECIFICATIONS

Model	Product	Power (W)	сст	CRI (typ.)	Lumens	LPW	Beam Angle
5.5PLSV/827/HYB/GX23	98403	5.5	Soft White 2700K	82	570	104	120°
5.5PLSV/830/HYB/GX23	98404	5.5	Warm White 3000K	82	600	109	120°
5.5PLSV/835/HYB/GX23	98405	5.5	Neutral White 3500K	82	600	109	120°
5.5PLSV/840/HYB/GX23	98406	5.5	Cool White 4000K	82	620	113	120°

^{*} Suitable for damp locations. Not for use where directly exposed to weather or water ** Not intended for use in enclosed fixtures