

DUPLEX RECEPTACLE TAMPER-RESISTANT

ELECTRIFYING YOUR WORLD WITH SAFETY IN MIND

- Available in 15A or 20A Duplex Style models
- Available in Regular or Decorator style
- Spring-loaded shutter system improves safety by blocking insertion of foreign objects
- Removable screw hole mounts enable custom fittings in existing electrical boxes
- 3-Wire setup with GREEN ground screw. Use with Copper Wire only
- 15A: Quick-wire Push-in and side-wire; 20A: Side-Wired installation
- Includes strap with removable ears to simplify product installs
- Suitable for standard residential and commercial grade applications
- Fits most standard sized wall plates (wall plate not included)
- Tested to meet UL498, CSA, and NEC standard compliant
- Environmental: flammability UL94, V2 Rating

Features



- Removable Mounting Screw Mounts enable custom fitting in any existing wiring boxes.
- Spring-loaded shutter keep children and animals safe by blocking access to anything other than two- or three-pronged plugs.
- Quick and easy installation in new or existing electrical boxes for residential and commercial grade use.

WARRANTY: 2 Year Warranty



SERE01AS-TR-W



SERE01BS-TR-W



Duplex Receptacle Tamper-Resistant

PRODUCT SKU	DESCRIPTION	AMPS	VOLTS	NEMA
SERE01AS-TR-W	15A DUPLEX TAMPER RESISTANT RECEPTACLE	15A	125VAC	5-15R
SERE01BS-TR-W	20A DUPLEX TAMPER RESISTANT RECEPTACLE	20A	125VAC	5-20R
SERE02AS-TR-W	15A DECORATOR TAMPER RESISTANT RECEPTACLE	15A	125VAC	5-15R
SERE02BS-TR-W	20A DECORATOR TAMPER RESISTANT RECEPTACLE	20A	125VAC	5-20R

AMPERAGE

- 15 amp
- 20 amp

VOLTAGE

125VAC

NEMA

- 5-15R
- 5-20R

POLES

2-Pole

STYLES

- Duplex
- Decorator

WIRING TYPE

- Quick-Wired Push-in
- Side Wired

PRODUCT DIMENSION

4.09 x 1.57 x 1.65 in

MATERIAL

Polycarbonate

SPECIFICATIONS SUBMITTAL

Job Name

Job Number

Notes