

Snow Melt Mats



Model Code:

SCM	20	48	24	-5
A	B	C	D	E
A: Snow Melt Mat				
B: 20 - 208V				
24 - 240V				
48 - 480V				
C: Watts per Sq/Ft				
D: Width of Mat				
E: Mat Length				

SCM Series Snow Melt Mat is designed for melting snow and ice for improved safety conditions.

SCM Snow Melt 208V Mat Features

- 20 Ft. Cold Lead, for use in concrete, asphalt & under pavers
- Single point connection, 10 year warranty
- Use in sidewalks, driveways, stairs, ramps, etc.
- Tefzel® Insulation, TPU Jacket, Emits zero EMFs

24"
208V

MODEL (24" WIDE)	UPC (093319)	MAT LENGTH	HEATED AREA (3" SPACING)	WATTS (48 W/FT²)	AMPS
SCM204824-4	42032	4.4 FT.	8.8 SQ. FT.	420	2.0
SCM204824-6	42033	6.3 FT.	12.5 SQ. FT.	600	2.9
SCM204824-8	42034	8.8 FT.	17.5 SQ. FT.	840	4.0
SCM204824-10	42035	10.6 FT.	21.3 SQ. FT.	1020	4.9
SCM204824-13	42036	13.1 FT.	26.3 SQ. FT.	1260	6.1
SCM204824-15	42037	15.6 FT.	31.3 SQ. FT.	1500	7.2
SCM204824-18	42038	18.1 FT.	36.3 SQ. FT.	1740	8.4
SCM204824-20	42039	20.0 FT.	40.0 SQ. FT.	1920	9.2
SCM204824-22	42040	22.5 FT.	45.0 SQ. FT.	2160	10.4
SCM204824-26	42041	26.3 FT.	52.5 SQ. FT.	2520	12.1
SCM204824-30	42042	30.6 FT.	61.3 SQ. FT.	2940	14.1
SCM204824-35	42043	35.0 FT.	70.0 SQ. FT.	3360	16.2
SCM204824-40	42044	40.0 FT.	80.0 SQ. FT.	3840	18.5
SCM204824-44	42045	44.4 FT.	88.8 SQ. FT.	4260	20.5
SCM204824-51	42046	51.3 FT.	102.5 SQ. FT.	4920	23.7
SCM204824-57	42047	57.5 FT.	115.0 SQ. FT.	5520	26.5

30"
208V

MODEL (30" WIDE)	UPC (093319)	MAT LENGTH	HEATED AREA (3" SPACING)	WATTS (48 W/FT²)	AMPS
SCM204830-3	42064	3.5 FT.	8.8 SQ. FT.	420	2.0
SCM204830-5	42065	5.0 FT.	12.5 SQ. FT.	600	2.9
SCM204830-7	42066	7.0 FT.	17.5 SQ. FT.	840	4.0
SCM204830-8	42067	8.5 FT.	21.3 SQ. FT.	1020	4.9
SCM204830-10	42068	10.5 FT.	26.3 SQ. FT.	1260	6.1
SCM204830-12	42069	12.5 FT.	31.3 SQ. FT.	1500	7.2
SCM204830-14	42070	14.5 FT.	36.3 SQ. FT.	1740	8.4
SCM204830-16	42071	16.0 FT.	40.0 SQ. FT.	1920	9.2
SCM204830-18	42072	18.0 FT.	45.0 SQ. FT.	2160	10.4
SCM204830-21	42073	21.0 FT.	52.5 SQ. FT.	2520	12.1
SCM204830-24	42074	24.5 FT.	61.3 SQ. FT.	2940	14.1
SCM204830-28	42075	28.0 FT.	70.0 SQ. FT.	3360	16.2
SCM204830-32	42076	32.0 FT.	80.0 SQ. FT.	3840	18.5
SCM204830-35	42077	35.5 FT.	88.8 SQ. FT.	4260	20.5
SCM204830-41	42078	41.0 FT.	102.5 SQ. FT.	4920	23.7
SCM204830-46	42079	46.0 FT.	115.0 SQ. FT.	5520	26.5

36"
208V

MODEL (36" WIDE)	UPC (093319)	MAT LENGTH	HEATED AREA (3" SPACING)	WATTS (48 W/FT²)	AMPS
SCM204836-2	42096	2.9 FT.	8.8 SQ. FT.	420	2.0
SCM204836-4	42097	4.2 FT.	12.5 SQ. FT.	600	2.9
SCM204836-5	42098	5.8 FT.	17.5 SQ. FT.	840	4.0
SCM204836-7	42099	7.1 FT.	21.3 SQ. FT.	1020	4.9
SCM204836-8	42100	8.8 FT.	26.3 SQ. FT.	1260	6.1
SCM204836-10	42101	10.4 FT.	31.3 SQ. FT.	1500	7.2
SCM204836-12	42102	12.1 FT.	36.3 SQ. FT.	1740	8.4
SCM204836-13	42103	13.3 FT.	40.0 SQ. FT.	1920	9.2
SCM204836-15	42104	15.0 FT.	45.0 SQ. FT.	2160	10.4
SCM204836-17	42105	17.5 FT.	52.5 SQ. FT.	2520	12.1
SCM204836-20	42106	20.4 FT.	61.3 SQ. FT.	2940	14.1
SCM204836-23	42107	23.3 FT.	70.0 SQ. FT.	3360	16.2
SCM204836-26	42108	26.7 FT.	80.0 SQ. FT.	3840	18.5
SCM204836-29	42109	29.6 FT.	88.8 SQ. FT.	4260	20.5
SCM204836-34	42110	34.2 FT.	102.5 SQ. FT.	4920	23.7
SCM204836-38	42111	38.3 FT.	115.0 SQ. FT.	5520	26.5

MODEL (24" WIDE)	UPC (093319)	MAT LENGTH	HEATED AREA (4" SPACING)	WATTS (36 W/FT²)	AMPS
SCM203624-5	42048	5.8 FT.	11.7 SQ. FT.	420	2.0
SCM203624-8	42049	8.3 FT.	16.7 SQ. FT.	600	2.9
SCM203624-11	42050	11.7 FT.	23.3 SQ. FT.	840	4.0
SCM203624-14	42051	14.2 FT.	28.3 SQ. FT.	1020	4.9
SCM203624-17	42052	17.5 FT.	35.0 SQ. FT.	1260	6.1
SCM203624-20	42053	20.8 FT.	41.7 SQ. FT.	1500	7.2
SCM203624-24	42054	24.2 FT.	48.3 SQ. FT.	1740	8.4
SCM203624-26	42055	26.7 FT.	53.3 SQ. FT.	1920	9.2
SCM203624-30	42056	30.0 FT.	60.0 SQ. FT.	2160	10.4
SCM203624-35	42057	35.0 FT.	70.0 SQ. FT.	2520	12.1
SCM203624-40	42058	40.8 FT.	81.7 SQ. FT.	2940	14.1
SCM203624-46	42059	46.7 FT.	93.3 SQ. FT.	3360	16.2
SCM203624-53	42060	53.3 FT.	106.7 SQ. FT.	3840	18.5
SCM203624-59	42061	59.2 FT.	118.3 SQ. FT.	4260	20.5
SCM203624-68	42062	68.3 FT.	136.7 SQ. FT.	4920	23.7
SCM203624-76	42063	76.7 FT.	153.3 SQ. FT.	5520	26.5

MODEL (30" WIDE)	UPC (093319)	MAT LENGTH	HEATED AREA (4" SPACING)	WATTS (36 W/FT²)	AMPS
SCM203630-4	42080	4.7 FT.	11.7 SQ. FT.	420	2.0
SCM203630-6	42081	6.7 FT.	16.7 SQ. FT.	600	2.9
SCM203630-9	42082	9.3 FT.	23.3 SQ. FT.	840	4.0
SCM203630-11	42083	11.3 FT.	28.3 SQ. FT.	1020	4.9
SCM203630-14	42084	14.0 FT.	35.0 SQ. FT.	1260	6.1
SCM203630-16	42085	16.7 FT.	41.7 SQ. FT.	1500	7.2
SCM203630-19	42086	19.3 FT.	48.3 SQ. FT.	1740	8.4
SCM203630-21	42087	21.3 FT.	53.3 SQ. FT.	1920	9.2
SCM203630-24	42088	24.0 FT.	60.0 SQ. FT.	2160	10.4
SCM203630-28	42089	28.0 FT.	70.0 SQ. FT.	2520	12.1
SCM203630-32	42090	32.7 FT.	81.7 SQ. FT.	2940	14.1
SCM203630-37	42091	37.3 FT.	93.3 SQ. FT.	3360	16.2
SCM203630-42	42092	42.7 FT.	106.7 SQ. FT.	3840	18.5
SCM203630-47	42093	47.3 FT.	118.3 SQ. FT.	4260	20.5
SCM203630-54	42094	54.7 FT.	136.7 SQ. FT.	4920	23.7
SCM203630-61	42095	61.3 FT.	153.3 SQ. FT.	5520	26.5

MODEL (36" WIDE)	UPC (093319)	MAT LENGTH	HEATED AREA (4" SPACING)	WATTS (36 W/FT²)	AMPS
SCM203636-3	42112	3.9 FT.	11.7 SQ. FT.	420	2.0
SCM203636-5	42113	5.6 FT.	16.7 SQ. FT.	600	2.9
SCM203636-7	42114	7.8 FT.	23.3 SQ. FT.	840	4.0
SCM203636-9	42115	9.4 FT.	28.3 SQ. FT.	1020	4.9
SCM203636-11	42116	11.7 FT.	35.0 SQ. FT.	1260	6.1
SCM203636-13	42117	13.9 FT.	41.7 SQ. FT.	1500	7.2
SCM203636-16	42118	16.1 FT.	48.3 SQ. FT.	1740	8.4
SCM203636-17	42119	17.8 FT.	53.3 SQ. FT.	1920	9.2
SCM203636-20	42120	20.0 FT.	60.0 SQ. FT.	2160	10.4
SCM203636-23	42121	23.3 FT.	70.0 SQ. FT.	2520	12.1
SCM203636-27	42122	27.2 FT.	81.7 SQ. FT.	2940	14.1
SCM203636-31	42123	31.1 FT.	93.3 SQ. FT.	3360	16.2
SCM203636-35	42124	35.6 FT.	106.7 SQ. FT.	3840	18.5
SCM203636-39	42125	39.4 FT.	118.3 SQ. FT.	4260	20.5
SCM203636-45	42126	45.6 FT.	136.7 SQ. FT.	4920	23.7
SCM203636-51	42127	51.1 FT.	153.3 SQ. FT.	5520	26.5

Snow Melt Mats



SCM Series Snow Melt Mat is designed for melting snow and ice for improved safety conditions.

SCM Snow Melt 240V Mat Features

- 20 Ft. Cold Lead, for use in concrete, asphalt & under pavers
- 10 year warranty, Emits zero EMFs (electromagnetic fields)
- Use in sidewalks, driveways, stairs, ramps, etc.
- Single point connection, Tefzel® Insulation, TPU Jacket



Model Code:

SCM	20	48	24	-5
A	B	C	D	E
A: Snow Melt Mat				
B: 20 - 208V				
24 - 240V				
48 - 480V				
C: Watts per Sq/Ft				
D: Width of Mat				
E: Mat Length				

	MODEL	UPC	MAT	HEATED AREA	WATTS		MODEL	UPC	MAT	HEATED AREA	WATTS	
	(24" WIDE)	(093319)	LENGTH	(3" SPACING)	(48 W/FT²)		AMPS	(24" WIDE)	(093319)	LENGTH	(4" SPACING)	(36 W/FT²)
24" 240V	SCM244824-5	42128	5.0 FT.	10.0 SQ. FT.	480	2.0	SCM243624-6	42144	6.7 FT.	13.3 SQ. FT.	480	2.0
	SCM244824-7	42129	7.5 FT.	15.0 SQ. FT.	720	3.0	SCM243624-10	42145	10.0 FT.	20.0 SQ. FT.	720	3.0
	SCM244824-10	42130	10.0 FT.	20.0 SQ. FT.	960	4.0	SCM243624-13	42146	13.3 FT.	26.7 SQ. FT.	960	4.0
	SCM244824-12	42131	12.5 FT.	25.0 SQ. FT.	1200	5.0	SCM243624-16	42147	16.7 FT.	33.3 SQ. FT.	1200	5.0
	SCM244824-15	42132	15.0 FT.	30.0 SQ. FT.	1440	6.0	SCM243624-20	42148	20.0 FT.	40.0 SQ. FT.	1440	6.0
	SCM244824-18	42133	18.1 FT.	36.3 SQ. FT.	1740	7.3	SCM243624-24	42149	24.2 FT.	48.3 SQ. FT.	1740	7.3
	SCM244824-20	42134	20.6 FT.	41.3 SQ. FT.	1980	8.3	SCM243624-27	42150	27.5 FT.	55.0 SQ. FT.	1980	8.3
	SCM244824-23	42135	23.1 FT.	46.3 SQ. FT.	2220	9.3	SCM243624-30	42151	30.8 FT.	61.7 SQ. FT.	2220	9.3
	SCM244824-25	42136	25.6 FT.	51.3 SQ. FT.	2460	10.3	SCM243624-34	42152	34.2 FT.	68.3 SQ. FT.	2460	10.3
	SCM244824-30	42137	30.6 FT.	61.3 SQ. FT.	2940	12.3	SCM243624-40	42153	40.8 FT.	81.7 SQ. FT.	2940	12.3
	SCM244824-35	42138	35.6 FT.	71.3 SQ. FT.	3420	14.3	SCM243624-47	42154	47.5 FT.	95.0 SQ. FT.	3420	14.3
	SCM244824-40	42139	40.6 FT.	81.3 SQ. FT.	3900	16.3	SCM243624-54	42155	54.2 FT.	108.3 SQ. FT.	3900	16.3
	SCM244824-46	42140	46.3 FT.	92.5 SQ. FT.	4440	18.5	SCM243624-61	42156	61.7 FT.	123.3 SQ. FT.	4440	18.5
	SCM244824-51	42141	51.3 FT.	102.5 SQ. FT.	4920	20.5	SCM243624-68	42157	68.3 FT.	136.7 SQ. FT.	4920	20.5
	SCM244824-59	42142	59.4 FT.	118.8 SQ. FT.	5700	23.8	SCM243624-79	42158	79.2 FT.	158.3 SQ. FT.	5700	23.8
	SCM244824-66	42143	66.9 FT.	133.8 SQ. FT.	6420	26.8	SCM243624-89	42159	89.2 FT.	178.3 SQ. FT.	6420	26.8
	30" 240V	MODEL	UPC	MAT	HEATED AREA	WATTS		MODEL	UPC	MAT	HEATED AREA	WATTS
		(30" WIDE)	(093319)	LENGTH	(3" SPACING)	(48 W/FT²)		AMPS	(30" WIDE)	(093319)	LENGTH	(4" SPACING)
SCM244830-4		42160	4.0 FT.	10.0 SQ. FT.	480	2.0	SCM243630-5	42176	5.3 FT.	13.3 SQ. FT.	480	2.0
SCM244830-6		42161	6.0 FT.	15.0 SQ. FT.	720	3.0	SCM243630-8	42177	8.0 FT.	20.0 SQ. FT.	720	3.0
SCM244830-8		42162	8.0 FT.	20.0 SQ. FT.	960	4.0	SCM243630-10	42178	10.7 FT.	26.7 SQ. FT.	960	4.0
SCM244830-10		42163	10.0 FT.	25.0 SQ. FT.	1200	5.0	SCM243630-13	42179	13.3 FT.	33.3 SQ. FT.	1200	5.0
SCM244830-12		42164	12.0 FT.	30.0 SQ. FT.	1440	6.0	SCM243630-16	42180	16.0 FT.	40.0 SQ. FT.	1440	6.0
SCM244830-14		42165	14.5 FT.	36.3 SQ. FT.	1740	7.3	SCM243630-19	42181	19.3 FT.	48.3 SQ. FT.	1740	7.3
SCM244830-16		42166	16.5 FT.	41.3 SQ. FT.	1980	8.3	SCM243630-22	42182	22.0 FT.	55.0 SQ. FT.	1980	8.3
SCM244830-18		42167	18.5 FT.	46.3 SQ. FT.	2220	9.3	SCM243630-24	42183	24.7 FT.	61.7 SQ. FT.	2220	9.3
SCM244830-20		42168	20.5 FT.	51.3 SQ. FT.	2460	10.3	SCM243630-27	42184	27.3 FT.	68.3 SQ. FT.	2460	10.3
SCM244830-24		42169	24.5 FT.	61.3 SQ. FT.	2940	12.3	SCM243630-32	42185	32.7 FT.	81.7 SQ. FT.	2940	12.3
SCM244830-28		42170	28.5 FT.	71.3 SQ. FT.	3420	14.3	SCM243630-38	42186	38.0 FT.	95.0 SQ. FT.	3420	14.3
SCM244830-32		42171	32.5 FT.	81.3 SQ. FT.	3900	16.3	SCM243630-43	42187	43.3 FT.	108.3 SQ. FT.	3900	16.3
SCM244830-37		42172	37.0 FT.	92.5 SQ. FT.	4440	18.5	SCM243630-49	42188	49.3 FT.	123.3 SQ. FT.	4440	18.5
SCM244830-41		42173	41.0 FT.	102.5 SQ. FT.	4920	20.5	SCM243630-54	42189	54.7 FT.	136.7 SQ. FT.	4920	20.5
SCM244830-47		42174	47.5 FT.	118.8 SQ. FT.	5700	23.8	SCM243630-69	42190	63.3 FT.	158.3 SQ. FT.	5700	23.8
SCM244830-53		42175	53.5 FT.	133.8 SQ. FT.	6420	26.8	SCM243630-71	42191	71.3 FT.	178.3 SQ. FT.	6420	26.8
36" 240V	MODEL	UPC	MAT	HEATED AREA	WATTS		MODEL	UPC	MAT	HEATED AREA	WATTS	
	(36" WIDE)	(093319)	LENGTH	(3" SPACING)	(48 W/FT²)		AMPS	(36" WIDE)	(093319)	LENGTH	(4" SPACING)	(36 W/FT²)
	SCM244836-3	42192	3.3 FT.	10.0 SQ. FT.	480	2.0	SCM243636-4	42208	4.4 FT.	13.3 SQ. FT.	480	2.0
	SCM244836-5	42193	5.0 FT.	15.0 SQ. FT.	720	3.0	SCM243636-6	42209	6.7 FT.	20.0 SQ. FT.	720	3.0
	SCM244836-6	42194	6.7 FT.	20.0 SQ. FT.	960	4.0	SCM243636-8	42210	8.9 FT.	26.7 SQ. FT.	960	4.0
	SCM244836-8	42195	8.3 FT.	25.0 SQ. FT.	1200	5.0	SCM243636-11	42211	11.1 FT.	33.3 SQ. FT.	1200	5.0
	SCM244836-10	42196	10.0 FT.	30.0 SQ. FT.	1440	6.0	SCM243636-13	42212	13.3 FT.	40.0 SQ. FT.	1440	6.0
	SCM244836-12	42197	12.1 FT.	36.3 SQ. FT.	1740	7.3	SCM243636-16	42213	16.1 FT.	48.3 SQ. FT.	1740	7.3
	SCM244836-13	42198	13.8 FT.	41.3 SQ. FT.	1980	8.3	SCM243636-18	42214	18.3 FT.	55.0 SQ. FT.	1980	8.3
	SCM244836-15	42199	15.4 FT.	46.3 SQ. FT.	2220	9.3	SCM243636-20	42215	20.6 FT.	61.7 SQ. FT.	2220	9.3
	SCM244836-17	42200	17.1 FT.	51.3 SQ. FT.	2460	10.3	SCM243636-22	42216	22.8 FT.	68.3 SQ. FT.	2460	10.3
	SCM244836-20	42201	20.4 FT.	61.3 SQ. FT.	2940	12.3	SCM243636-27	42217	27.2 FT.	81.7 SQ. FT.	2940	12.3
	SCM244836-23	42202	23.8 FT.	71.3 SQ. FT.	3420	14.3	SCM243636-31	42218	31.7 FT.	95.0 SQ. FT.	3420	14.3
	SCM244836-27	42203	27.1 FT.	81.3 SQ. FT.	3900	16.3	SCM243636-36	42219	36.1 FT.	108.3 SQ. FT.	3900	16.3
	SCM244836-30	42204	30.8 FT.	92.5 SQ. FT.	4440	18.5	SCM243636-41	42220	41.1 FT.	123.3 SQ. FT.	4440	18.5
	SCM244836-34	42205	34.2 FT.	102.5 SQ. FT.	4920	20.5	SCM243636-45	42221	45.6 FT.	136.7 SQ. FT.	4920	20.5
	SCM244836-39	42206	39.6 FT.	118.8 SQ. FT.	5700	23.8	SCM243636-52	42222	52.8 FT.	158.3 SQ. FT.	5700	23.8
	SCM244836-44	42207	44.6 FT.	133.8 SQ. FT.	6420	26.8	SCM243636-59	42223	59.4 FT.	178.3 SQ. FT.	6420	26.8

Snow Melt Mats



Model Code:

SCM	20	48	24	-5
A	B	C	D	E
A: Snow Melt Mat				
B: 20 - 208V				
24 - 240V				
48 - 480V				
C: Watts per Sq/Ft				
D: Width of Mat				
E: Mat Length				



SCM Series Snow Melt Mat is designed for melting snow and ice for improved safety conditions.

SCM Snow Melt 480V Mat Features

- 20 Ft. Cold Lead, for use in concrete, asphalt & under pavers
- 10 year warranty, Emits zero EMFs (electromagnetic fields)
- Use in sidewalks, driveways, stairs, ramps, etc.
- Single point connection, Tefzel® Insulation, TPU Jacket

	MODEL	UPC	MAT	HEATED AREA	WATTS		MODEL	UPC	MAT	HEATED AREA	WATTS	
	(24" WIDE)	(093319)	LENGTH	(3" SPACING)	(48 W/FT²)		AMPS	(24" WIDE)	(093319)	LENGTH	(4" SPACING)	(36 W/FT²)
24" 480V	SCM484824-10	42448	10.0 FT.	20.0 SQ. FT.	960	2.1	SCM483624-13	42427	13.3 FT.	26.7 SQ. FT.	960	2.1
	SCM484824-25	42449	25.0 FT.	50.0 SQ. FT.	2400	5.1	SCM483624-33	42428	33.3 FT.	66.7 SQ. FT.	2400	5.1
	SCM484824-41	42450	41.3 FT.	82.5 SQ. FT.	3960	8.4	SCM483624-55	42429	55.0 FT.	110.0 SQ. FT.	3960	8.4
	SCM484824-61	42451	61.3 FT.	122.5 SQ. FT.	5880	12.5	SCM483624-81	42430	81.7 FT.	163.3 SQ. FT.	5880	12.5
	SCM484824-91	42452	91.9 FT.	183.8 SQ. FT.	8820	18.6	SCM483624-122	42431	122.5 FT.	245.0 SQ. FT.	8820	18.6
	SCM484824-102	42453	102.5 FT.	205.0 SQ. FT.	9840	20.9	SCM483624-136	42432	136.7 FT.	273.3 SQ. FT.	9840	20.9
	SCM484824-117	42454	117.5 FT.	235.0 SQ. FT.	11280	23.9	SCM483624-156	42433	156.7 FT.	313.3 SQ. FT.	11280	23.9
30" 480V	MODEL	UPC	MAT	HEATED AREA	WATTS		MODEL	UPC	MAT	HEATED AREA	WATTS	
	(30" WIDE)	(093319)	LENGTH	(3" SPACING)	(48 W/FT²)		AMPS	(30" WIDE)	(093319)	LENGTH	(4" SPACING)	(36 W/FT²)
	SCM484830-82	42455	8.0 FT.	20.0 SQ. FT.	960	2.1	SCM483630-10	42434	10.7 FT.	26.7 SQ. FT.	960	2.1
	SCM484830-20	42456	20.0 FT.	50.0 SQ. FT.	2400	5.1	SCM483630-26	42435	26.7 FT.	66.7 SQ. FT.	2400	5.1
	SCM484830-33	42457	33.0 FT.	82.5 SQ. FT.	3960	8.4	SCM483630-44	42436	44.0 FT.	110.0 SQ. FT.	3960	8.4
	SCM484830-49	42458	49.0 FT.	122.5 SQ. FT.	5880	12.5	SCM483630-65	42437	65.3 FT.	163.3 SQ. FT.	5880	12.5
	SCM484830-73	42459	73.0 FT.	183.8 SQ. FT.	8820	18.6	SCM483630-98	42438	98.0 FT.	245.0 SQ. FT.	8820	18.6
SCM484830-82	42160	82.0 FT.	205.0 SQ. FT.	9840	20.9	SCM483630-109	42439	109.3 FT.	273.3 SQ. FT.	9840	20.9	
SCM484830-94	42461	94.0 FT.	235.0 SQ. FT.	11280	23.9	SCM483630-125	42440	125.3 FT.	313.3 SQ. FT.	11280	23.9	
36" 480V	MODEL	UPC	MAT	HEATED AREA	WATTS		MODEL	UPC	MAT	HEATED AREA	WATTS	
	(36" WIDE)	(093319)	LENGTH	(3" SPACING)	(48 W/FT²)		AMPS	(36" WIDE)	(093319)	LENGTH	(4" SPACING)	(36 W/FT²)
	SCM484836-6	42462	6.7 FT.	20.0 SQ. FT.	960	2.1	SCM483636-8	42441	8.9 FT.	26.7 SQ. FT.	960	2.1
	SCM484836-16	42463	16.7 FT.	50.0 SQ. FT.	2400	5.1	SCM483636-22	42442	22.2 FT.	66.7 SQ. FT.	2400	5.1
	SCM484836-27	42464	27.5 FT.	82.5 SQ. FT.	3960	8.4	SCM483636-36	42443	36.7 FT.	110.0 SQ. FT.	3960	8.4
	SCM484836-40	42465	40.8 FT.	122.5 SQ. FT.	5880	12.5	SCM483636-54	42444	54.4 FT.	163.3 SQ. FT.	5880	12.5
	SCM484836-61	42466	61.3 FT.	183.8 SQ. FT.	8820	18.6	SCM483636-81	42445	81.7 FT.	245.0 SQ. FT.	8820	18.6
	SCM484836-68	42467	68.3 FT.	205.0 SQ. FT.	9840	20.9	SCM483636-91	42446	91.1 FT.	273.3 SQ. FT.	9840	20.9
SCM484836-78	42468	78.3 FT.	235.0 SQ. FT.	11280	23.9	SCM483636-104	42447	104.4 FT.	313.3 SQ. FT.	11280	23.9	

More voltages available. Call for additional information

****Controls and thermostats should always be used with King heating cable systems.**