

PROJECT NAME: _____ CAT. #: _____
 NOTES: _____ FIXTURE SCHEDULE: _____

Slim Downlight Baffle Style SDB Series



Description:

The CCT Selectable Slim Downlights mount directly into the ceiling, requiring no can. With a simple flick of a switch on the remote driver junction box, installers can choose from 2700K, 3000K, 3500K, 4000K or 5000K as CCT to suit various application needs. Low profile and easy to install, the Flush style fixture is Energy Star, Wet locations, IC rated and supports Title 24. Its edge lit optics provide an even and low glare illumination with an outstanding color rendering, making it the ideal choice for hospitality, retail, offices and multi-unit residential spaces.

Features:

- 2700K/ 3000K/3500K/4000K/5000K CCT Selectable
- CRI: ≥90
- Beam angle: ~110°
- Universal mounting plate available
- Goof rings available for additional coverage
- Mounts into ceiling without the use of a separate housing
- Field installable Emergency Battery back up kit available (includes a test switch and the charge indicator kit, no cover)

Dimming:

- 120V option available with 120V triac dimming

Construction:

- Die cast Aluminum housing
- Plastic Lens

Listings:

- ETL Listed for wet locations
- ENERGY STAR certified
- IC rated
- Airtight construction
- Supports T24 Part 6 high efficacy lighting requirements

Ordering Information

FAMILY	SHAPE	SIZE	WATTAGE (NOMINAL)	CRI+ COLOR SELECTABLE	TRIM
SDB= Slim Downlights Baffle style	R= Round	4= 4"	12= 12W	9CS= 90 CRI, 2700/3000/3500/4000/5000 (Default is 3000K)	W= White
		6= 6"	18= 18W		
		8= 8"			

Stocked Items

ORDER CODE	MODEL NUMBER	ENERGY STAR #
105304	SDBR4129CSW	2371978
105361	SDBR6129CSW	2371979
105306	SDBR8189CSW	2371981

Dimming Compatibility

	DIMMER MODELS
Lutron	DVCL-153PR-WH, CTCL-153PDH-WH, TGCL-153PH-WH, MACL-153MH-WH, P-PKG1W-WH-R
Leviton	R62-06674-P0W, R12-06672-1LW, R50-IPL06-10M
Eaton	AAL06-C1, SAL06P-LA-K



5-year standard warranty (further details available at www.maxlite.com/warranties)
 Product may be eligible for a warranty extension to 10 years, for an additional fee. Contact MaxLite for details.

Slim Downlight Baffle Style

SDB Series

Accessories

ORDER CODE	MODEL NUMBER	DESCRIPTION	IMAGE
105886	SD-UNVTEMPLATE	Slim Downlights, Rough in Template, Universal 4", 6", 8"	
14098874	RCF-4	4" Commercial Recessed Frame, New Construction	
14098875	RCF-6	6" Commercial Recessed Frame New Construction	
14098876	RCF-8	8" Commercial Recessed Frame, New Construction	
100298	EBUUP15007N0100	Emergency Battery Back up, 07W, 100-347V, Field installable	
105651	SD-EXTCABLE24	Slim Downlights, Extension Cable, 24", Plenum Rated F1 (Interconnect Up to Qty 3)	
14099683	RR-XRING4	4" Extra Wide Trim Ring	
14099684	RR-XRING6	6" Extra Wide Trim Ring	
14099685	RR-XRING8	8" Extra Wide Trim Ring	
105025	SDBR-LTRIM4	Slim Downlights, Baffle Style, 4", Black Trim	
105590	SDBR-LTRIM6	Slim Downlights, Baffle Style, 6", Black Trim	
105591	SDBR-LTRIM8	Slim Downlights, Baffle Style, 8", Black Trim	

Specifications

	SDBR4129CSW	SDBR6129CSW	SDBR8189CSW
Power Consumption	12W	12W	18W
Equivalency	75W INC	75W INC	125W INC
Lumens Delivered	800 lm	900 lm	1500 lm
Lumens Battery Mode	750 lm	850 lm	1350 lm
Efficacy	67 lm/w	75 lm/w	83 lm/w
Beam Angle		-100°	
CRI		≥ 90	
Color Temperature (K)	2700K/3000K/3500K/4000K/5000K (Default is 3000K)		
L70 Lumen maintenance		≥ 50,000	
Power Factor		≥ 0.9	
Input Voltage		120V, 60Hz	
Dimming		Triac Dimming Range: 10%-100%	
Operating Temperature		-4°F TO 104°F (-20°C TO 40°C)	
Listings	cETLus, FCC, Title 24 Compliant, JA8, IC Rated, Airtight		
Environment	UL listed for Wet location		
Warranty	5 Year Warranty		

Dimensions:

