

PROJECT NAME: _____ CAT. #: _____
 NOTES: _____ FIXTURE SCHEDULE: _____

LED Enclosed Rated Omnidirectional A-Lamp

A19 Gen 1S Series



Product Description:

MaxLite's LED enclosed rated Omnidirectional A-Line lamp replicate true A19 incandescents. They are suited to a wide variety of residential and commercial applications, including pendants, wall sconces, table and floor lamps.

Features:

- Dimmable down to 10%
- Suitable for damp locations
- Suitable for use in enclosed luminaires

Applications:

- Pendants
- Table and Floor lamps
- Sconces

WATTAGE	WIDTH / W (INCHES)	HEIGHT / H (INCHES)
8W	2.4	4.3
13W	2.4	4.6

Ordering Information

FAMILY	BASE	DIMMABILITY	CCT	GENERATION
E8A19= 8W, A19 E13A19= 13W, A19	(OMIT)= E26	DLED= Dimmable LED	27= 2700K 30= 3000K 40= 4000K 50= 5000K	/G1S= Generation 1S
		D= Dimmable	27= 2700K 50= 5000K	/4P/WS1S= Generation 1S, 4 Pack Wingstack
E8A19= 8W, A19		DLED= Dimmable LED	27= 2700K	/G1/BPS= Generation 1S, Bulk Pack /G1/4PS= Generation 1S, 4 Pack

Stocked Items

ORDER CODE	MODEL NUMBER	ENERGY STAR #
106890	E8A19DLED30/G1S	2382486
106889	E8A19DLED27/G1S	2382485
106901	E8A19DLED27/G1/BPS	2382489
106888	E8A19D50/4P/WS1S	2382484
106887	E8A19D27/4P/WS1S	2382483



5-year standard warranty (further details available at www.maxlite.com/warranties)

Product may be eligible for a warranty extension to 10 years, for an additional fee. Contact MaxLite for details.

LED Enclosed Rated Omnidirectional A-Lamp

A19 Gen 1S Series

Specifications

	E8A19DLEDxx/G1S	E13A19DLED30/G1S
Base Type	E26	
Nominal Input Power	8W	13W
Equivalency	60W Incandescent	100W Incandescent
Lumens Delivered	800 lm	1600 lm
Efficacy	89 lm/W	120 lm/W
CRI	≥80	
Color Temperature/CCT	2700K, 3000K, 4000K, 5000K	
Input Wattage	120V 60Hz	
Power Factor	≥0.60	≥0.90
Operating Temperature	-4°F to 104°F (-20°C to 40°C)	
Dimmable	Yes, Triac 10-100%	
Lumen Maintenance/L70	≥25,000Hrs	
Certifications	ENERGY STAR, cETLus listed, FCC	
Environment	Suitable for damp locations, Suitable for use in enclosed luminaires	
Warranty	5 Years	

Dimming Compatibility

MANUFACTURER	MODELS
Lutron	PD-3PCL, DVCL-153PR-WH, CTCL-153PDH-WH-C, S-600H-WH-CSA, D-600, SCL-153P
Leviton	6674, 6672, RDL06