

PROJECT NAME: _____ CAT. #: _____
 NOTES: _____ FIXTURE SCHEDULE: _____

LED Directional 6.5W MR16 JA8 GU10 Base



Product Description:

Providing years of high-quality light at a fraction of the energy consumed by halogen lamps, MaxLite's LED MR16 Lamps are ideal for directional lighting in retail, hospitality and residential spaces.

Features:

- Construction: Aluminum Heatsink and Polycarbonate diffuser
- Suitable for Damp locations
- Dimmable down to 10%

Applications:

- Home
- Office
- Retail
- Hospitality
- Accent/display lighting
- Track lighting

Ordering Information

FAMILY	BASE	DIMMABILITY	CRI & COLOR TEMP	BEAM	COMPLIANCE	FINISH	GENERATION
6.5MR= 6.5W LED MR16	G= GU10	D= Dimmable	927= 90CRI 2700K 930= 90CRI 3000K	FL= Flood	/JA8= JA8-2019-E	[BLANK]= White	/G3= Generation 3

Dimmer List

MODEL NUMBER	ORDER CODE
Lutron	DVCL-153P-WH, TGCL-153P-WH, DVCL-153PR-WH, CTCL-153PDH-WH, P-PKG1W-WH, DIVA DVELV-300P-WH, SKYLARK SLV-600P-WH
Leviton	LIGHT ALMOND NO.6672 600W, WHITE NO.IPL06 600W, TSM10-012-1LW, RDL06-001-10Z, DSE06-001-10Z, DDMX1-011-BLZ, DDE06-BLZ 600W, SLIDE DIMMER SURESLIDE
Legrand	RHCL453PW



5-year standard warranty (further details available at www.maxlite.com/warranties)
 Product may be eligible for a warranty extension to 10 years, for an additional fee. Contact MaxLite for details.



LED Directional 6.5W MR16 JA8 GU10 Base

Specifications

	6.5MRGD927FL/JA8/G3	6.5MRGD930FL/JA8/G3
Power Consumption	6.5W	
Lumens Delivered	≥500	
Efficacy	≥70	
Beam Angle	40°	
CBCP	≥740	
CRI	≥90	
CCT (K)	2700K	3000K
L70 Lifetime (hrs)	≥25,000Hrs	
Lens	Halo Frosted Polycarbonate	
Voltage	120V 60Hz	
Power Factor	≥0.9	
Operating Temperature	-4°F to 104°F (-20°C to 40°C)	
Certifications	JA8-2019-E, TITLE 20 Listed, cULus Listed, FCC, RoHS	
Environment	Suitable for Damp Locations	
Warranty	5 Years	