

PROJECT NAME: _____
 NOTES: _____

CAT. #: _____
 FIXTURE SCHEDULE: _____

LED Jelly Jar CCT Selectable



Product Description

The LED Jelly Jar is an all-in-one replacement for small incandescent and CFL fixture applications. An adjustable knuckle allows the luminaire to rotate from 0 to 180 degrees, enabling it to be mounted as a pendant, ceiling or wall fixture. Additionally, it features CCT selectability providing 3 choices for color temperatures to suit customer preference. The innovative design offers easy maintenance and years of high-quality illumination with a rugged IP65 die cast aluminum housing and wire guard.

Features

- 3000K/4000K/5000K CCT Selectable
- 0-10V dimmable driver
- All-in-One pendant, ceiling and wall mount
- 0 to 180 degrees adjustable with a lock-in mechanism to allow field setting at a specific angle
- Five ½ NPT knockouts available for pipe or conduit mounting

Voltage

- 120-277V

Construction

- Die cast aluminum housing with corrosion resistant polyester powder coat finish
- Frosted glass lens
- IP65

Listings

- UL Listed for Wet Locations, Outdoor

Ordering Information

FAMILY	STYLE	WATTAGE	VOLTAGE	-	CCT	FINISH	COMPLIANCE
JJ = Jelly Jar	X = Ceiling/Wall Mount	21 = 21W	U = 120-277V	-	CS = 3000K/4000K/5000K	G = Gray	BLANK = Not TAA TA = TAA Compliant

Stocked Items

ORDER CODE	MODEL NUMBER	DLC ID
113730	JJX21U-CSGTA	S-QQY8SZ

LED Jelly Jar

CCT Selectable

Specifications

Specifications	JJX21U-CSG		
	3000K	4000K	5000K
CCT*	3000K	4000K	5000K
Lumens Delivered (lm)	2,439 lm	2,555 lm	2,551 lm
Nominal Efficacy (lm/W)	115 lm/W	124 lm/W	120 lm/W
CRI	≥80		
Equivalency	150W INC		
L70 Lifetime (hrs)	50,000 hrs		
Wattage (W)	21W		
Power Factor	≥0.9		
Input Voltage	120-277V		
Housing	Die Cast Aluminum		
Lens Plastic	Glass		
Operating Temperature	-40°F to 131°F (-40°C to 55°C)		
Listings	cLus, IP65, DLC, FCC		
Environment	Wet location, outdoor		
Warranty	5 Years warranty. Check maxlite.com/warranties for details		
Case Qty	6 pcs.		

*5000K CCT Default

Dimensions

