


FLUSH MOUNT TRADITIONAL STYLE - LAMP INCLUDED



Nickel Finish



White Finish



PRODUCT DESCRIPTION:

LED Flush Mount Ceiling Fixtures provide exceptional performance in general lighting applications for residential, multi-unit residential, hotels, and commercial properties. The series is available in nickel and white finishes with a high-transmission glass lens to complement virtually any décor. This bulb in a box solution comes prepackaged with JA8 compliant LED bulbs for ease of installation and guarantee of high CRI, flicker free LED performance.



FEATURE:

- JA8 Lamp included - 2 x E12A19D927/JA8

DIMMING:

- 120V option available with 120V triac dimming (10%)

CONSTRUCTION:

- Die form steel housing
- Frosted glass lens
- Powder coat finish

LISTINGS:

- ETL listed for Damp Locations, Indoor
- ENERGY STAR certified
- Supports T24 Part 6 high efficacy lighting requirements.

WARRANTY:

5-year standard warranty (further details available at www.maxlite.com/warranties)
Product may be eligible for a warranty extension to 10 years, for an additional fee. Contact MaxLite for details.

ORDERING STRUCTURE

FAMILY	TYPE	SIZE	STYLE	FINISH	VOLTAGE	LAMP	GENERATION
ML2= Ceiling Flush Mounts	E= Edison Base E26 Bulb included	242= 2 x 11W Lamps	TR= Traditional	NI= Nickel WH= White	[BLANK]= 120V, Triac dimming	27= 2700K, 90 CRI, JA8	-V2= Gen 2

ORDER CODES

ORDER CODE	MODEL NUMBER	ENERGY STAR PRODUCT ID
1408622	ML2E242TRNI27-V2	2334206
1408623	ML2E242TRWH27-V2	2334206

COMPATIBLE DIMMERS

BRAND	MODEL
LUTRON	YCL-153P-WH, AYCL-153PH, DVCL-153P-WH, DVWCL-153PH-WHC, S-603PH-WH, SCL-153PH-WH, TGCL-153PH-WH
LEVITON	6631, 6672, 6683, 603-6631-A, 6631-A, 6683-10Z, IPI06-1LZ, IPI10-1LZ, IPL06

SPECIFICATIONS		ML2E242
SPECIFICATION	DETAILS	
Nominal Wattage (W)	24	
Lumens Delivered (lm)	2200	
Equivalency	2 x 75W INC	
Efficacy (lm/W)	92	
Beam Angle	120°	
CRI	≥90	
Color Temperature (K)	2700K	
L70 Lifetime (hrs)	≥25,000 Hrs	
Voltage	120V, TRIAC Dimming, 10%	
Power Factor	≥0.90	
Housing	Die Form Steel metal	
Lens	Frosted Glass	
Mounting	Ceiling	
Operating Temperature	0°F to 104°F	
Listings	ENERGY STAR, Title 24, cETLus, FCC	
Environment	Damp locations, Indoor	
Warranty	5 Years	