

PROJECT NAME:	.CATALOG NUMBER:
NOTES:	_FIXTURE SCHEDULE:

Page: 1 of 2

LED 3-WAY OMNIDIRECTIONAL

3-WAY SERIES













PRODUCT DESCRIPTION:

MaxLite's LED 3-way Lamp offers three distinct levels of light and dimmability to suit any task or mood. For use in standard 3-way fixtures, the LED lamps replicate the beautiful, warm light of an incandescent bulb while consuming 85 percent less energy and lasting 25 times longer.

FEATURES:

- Input Wattage: 4W/9W/15W
- Replacement for 40W/60W/100W Incandescent
- Lumens: 500/1000/1600
- CCT: 2700K & 3000K
- CRI: 91
- ENERGY STAR Certified
- For use in 3-way light fixtures (non-dimmable)
- 300° beam angle
- Saves more than 85 percent on energy
- Power factor: ≥ 0.90
- Base: E26 (medium)
- Not for use in totally enclosed luminaires
- Suitable for damp locations
- Ideal for indoor application
- Warranty: 3 year limited
- Life hours (L70 standards): 25,000 hours

APPLICATIONS:

- Table and floor lamps
- Pendants

MODEL SELECTION (Full list of order codes on pg. 2)	Typical order example: 15A21/3WLED927				
15A21/3W	LED				
FAMILY	DIMMABILITY	COLOR RENDER INDEX & CCT			
15A21/3W= 15 watts A21, 3-Way	LED= Non-Dimmable	927= 91 CRI, 2700K 930= 91 CRI, 3000K			



LED 3-WAY OMNIDIRECTIONAL 3-WAY SERIES

Page: 2 of 2

SPECIFICATIONS:		15A21/3WLED9xx			
ITEM	SPECIFICATION	DETAILS			
	Power Consumption	4W/9W/15W			
	Lumens Delivered	500/1000/1600			
GENERAL PERFORMANCE	CRI	91			
	Color Temperature (CCT) 2700K, 3000K				
	Lumen Maintenance (L70)	25,000 Hours			
ELECTRICAL	Power Factor	≥0.90			
ELECTRICAL	Input Voltage	120V			
PHYSICAL	Base Type	E26			
PHYSICAL	Operating Temperature	-4°F - 104°F			
	Certification	cULus Listed, RoHS compliant, T20, ES V2.1			
CERTIFICATION	Environment	Dry, Damp			
	Warranty	3 Year Limited			

ORDERING:

ORDER CODE	MODEL	ENERGY STAR	WATTS	EQUIVALENCY	DELIVER LUMENS	CRI	DIMENSIONS (W" x MOL")	ССТ
14098774	15A21/3WLED927	\Rightarrow	4W/9W/15W	40/60/100W Inc.	500/1000/1600	91	2.83" x 5.47"	2700K
14098775	15A21/3WLED930	\Rightarrow	4W/9W/15W	40/60/100W Inc.	500/1000/1600	91	2.83" x 5.47"	3000K



★ ENERGY STAR Certified