



	Produ	ct Spec	
Category	LED T8 Type B (Ballast ByPass)		
Item Code	4557		
Stock Code	LED9T8/24FR11/850/UNV	PICTURE	
Mounting	G13		
Housing Color	White Plastic + Frosted Glass		

Electric Characteristics		Photometric Characteristics		
Rated Wattage (W)	9W ± 10%	Lumen (lm)	1150	
Гested Wattage (W)	9	Efficacy (lm/w)	128	
nput Voltage (V)	120~277	CRI	82	
oltage Frequency (Hz)	50/60	сст (к)	5000	
nput Current (A)	0.078	Beam Angle (∘)	210	
Power Factor	>0.9	General Cha	General Characteristics	
Replacement Wattage (W)	-	Operating Temperature	-4°F~113°F	
Surge protect level	1.5KV	Storage Temperature	-40°F~185°F	
Dimmable	No	IP rating	UL Damp Location	
THD	<20	Rated Life	50000 hrs	
		Warranty	5 years	
Product Dimensions		Suggested Accessory		
Weight (lbs.)				
Height (in)				
Length (in)	23.7			
Width (in)	23.7			
Width (in) Mounting Height (ft)				
Width (in)				
Width (in) Mounting Height (ft)				
Width (in)  Mounting Height (ft)  Cable Length (ft)	1	lifications		
Width (in)  Mounting Height (ft)  Cable Length (ft)  UL/ETL	1	lifications  LM79	٧	
Width (in)  Mounting Height (ft)  Cable Length (ft)	1 Qual	T I	V V	
Width (in)  Mounting Height (ft)  Cable Length (ft)  UL/ETL  Energy Star	1 Qual	LM79		
Width (in) Mounting Height (ft) Cable Length (ft)  UL/ETL Energy Star	Qual UL	LM79 LM80	٧	
Width (in)  Mounting Height (ft)  Cable Length (ft)  UL/ETL  Energy Star  DLC  CEC	Qual UL	LM79 LM80 IES File	٧	
Width (in) Mounting Height (ft)	Qual UL	LM79  LM80  IES File  FDA	٧	