

	Prod	uct Spec	
Category	Slim Canopy		Aug.
Item Code	9212	7	
Stock Code	LED-FXSCM100/50K/BK	PICTURE	
Mounting	Ceiling		
Housing Color	Black		

Housing Color	Black				
Electric	Characteristics	Photometric	c Characteristics		
Rated Wattage (W)	100	Lumen (lm)	12516		
Tested Wattage (W)	99.46	Efficacy (lm/w)	126		
Input Voltage (V)	120~277	CRI	70		
Voltage Frequency (Hz)	50/60	сст (к)	5000		
Input Current (A)	1.05	Beam Angle (°)	Parking Garage		
Power Factor	>0.9	General C	General Characteristics		
Replacement Wattage (W)	-	Operating Temperature	-22°F~131°F		
Surge protect level	4KV	Storage Temperature	-40°F~140°F		
Dimmable	1-10V	IP rating	IP65		
THD	<20%	Rated Life	50000 hrs		
		Warranty	5 years		
Product Dimensions		Suggested Accessory			
Weight (lbs.)	8.2	Microw	Microwave Sensor		
Height (in)	4.5	EM	l driver		
Length (in)	13				
Width (in)	13				
Mounting Height (ft)					
Cable Length (ft)					
	Qual	ifications			
UL/ETL	UL	LM79	٧		
		LM80	V		
Energy Star		Livido			
	V4.4 Premium	IES File	٧		
DLC	V4.4 Premium				
DLC CEC	V4.4 Premium	IES File			
Energy Star DLC CEC JA8 FCC	V4.4 Premium √	IES File FDA			