NOTURALED[®] Product Engineering Spec

	1100	uct Spec	1		
Category	Premium LED Panel				
Item Code	9221				
Stock Code	LED-FXPNL36/2X4/840	PICTURE	1		
Mounting	Recessed				
Housing Color	White				
Electri	c Characteristics		Photometr	ic Characteristics	
Rated Wattage (W)	36	Lumen (lm)		4500	
Tested Wattage (W)	36		Efficacy (lm/w)	125	
Input Voltage (V)	120~277		CRI	80	
Voltage Frequency (Hz)	50/60		ССТ (К)	4000	
Input Current (A)	0.3		Beam Angle (°)	110	
Power Factor	>0.9			Characteristics	
Replacement Wattage (W)	90~100	Operatir	ng Temperature	-4°F~104°F	
Surge protect level	>1000V (L-N)	Storag	ge Temperature	-4°F~140°F	
Dimmable	1-10V		IP rating	IP20	
THD	≤20%		Rated Life	50000 hrs	
			Warranty	5 years	
		-			
Product Dimensions			Suggested Accesory		
Weight (lbs.)			Surface Installation Frame		
- 9 - ()			Flange Mount		
Height (in)	1.69				
	1.69 47.8		El	M Driver	
Height (in)			EI	M Driver	
Height (in) Length (in)	47.8		El	M Driver	
Height (in) Length (in) Width (in)	47.8		El	M Driver	
Height (in) Length (in) Width (in) Mounting Height (ft)	47.8		EI	M Driver	
Height (in) Length (in) Width (in) Mounting Height (ft)	47.8		EI	M Driver	
Height (in) Length (in) Width (in) Mounting Height (ft)	47.8 23.82	fications	E	M Driver	
Height (in) Length (in) Width (in) Mounting Height (ft) Cable Length (ft)	47.8 23.82	fications	E1	M Driver /	
Height (in) Length (in) Width (in) Mounting Height (ft) Cable Length (ft) UL/ETL	47.8 23.82 Quali	fications			
Height (in) Length (in) Width (in) Mounting Height (ft) Cable Length (ft) UL/ETL Energy Star	47.8 23.82 Quali	fications	LM79	/	
Height (in) Length (in) Width (in) Mounting Height (ft) Cable Length (ft) UL/ETL Energy Star DLC	47.8 23.82 Quali	fications	LM79 LM80	/ / /	
Height (in) Length (in) Width (in) Mounting Height (ft) Cable Length (ft) UL/ETL Energy Star DLC CEC	47.8 23.82 Quali	fications	LM79 LM80 IES File	/ / /	
Height (in) Length (in) Width (in) Mounting Height (ft)	47.8 23.82 Quali	fications	LM79 LM80 IES File FDA	/ / /	