

	Produ	ct Spec	
Category	Commercial Downlight		
Item Code	9352		
Stock Code	LED6CRL21SW-150L930/MV	PICTURE	
Mounting	recessed		
Housing Color	White		

Electri	ic Characteristics	Photometric Ch	aracteristics	
Rated Wattage (W)	21/14/9	Lumen (lm)	1500/1050/750	
Tested Wattage (W)	21/14/9	Efficacy (lm/w)	71	
Input Voltage (V)	120-277	CRI	90	
Voltage Frequency (Hz)	60	сст (к)	3000	
nput Current (A)	0.2	Beam Angle (∘)	110	
Power Factor	>0.9	General Characteristics		
Replacement Wattage (W)		Operating Temperature	5°F~104°F	
Surge protect level		Storage Temperature	-4°F~104°F	
Dimmable	No	IP rating	UL Wet Location	
THD	<20%	Rated Life	50000 hrs	
		Warranty	5 years	
	uct Dimensions	Suggested A	Suggested Accessory	
Weight (lbs.)	0.39			
Height (in)	4.17			
Length (in)	7.48			
Width (in)	7.48			
Mounting Height (ft)				
Mounting Height (ft) Cable Length (ft)				
Cable Length (ft)	Qual	ifications		
Cable Length (ft) UL/ETL	Qual	ifications LM79	٧	
Cable Length (ft) UL/ETL Energy Star	1		√ √	
Cable Length (ft) UL/ETL Energy Star DLC	ETL	LM79		
Cable Length (ft) UL/ETL Energy Star	ETL	LM79 LM80	٧	
Cable Length (ft) UL/ETL Energy Star DLC CEC	ETL	LM79 LM80 IES File	٧	
	ETL	LM79 LM80 IES File FDA	٧	