

CWP CUT-OFF WALL PACK

PROJECT: _____

SCHEDULE: _____ DATE: _____

PREPARE BY: _____

NOTES: _____

DESCRIPTION

naturaLED® cut-off wallpack comes in rugged cast-aluminum housing with excellent thermal design. Our CWP product offers a popular but classic appearance with sleek angle design. Delivering up to 14,667 lumens with different wattages options: 40W, 60W, 80W, 120W. Replacing up to 750-watt metal halide luminaires and provides energy saving up to 72%. Our CWP is ideal for outdoor applications such as carports, loading areas, driveways, parking areas, and pathways. Suggested for wall mounting minimum above four feet from ground.



Rated Life 50,000 Hours
Warranty 5 Years



APPLICATIONS

Security, Pathway, Perimeter, Entryway, Area Lighting, and building facades

FEATURES

- DLC Premium Qualified
- IP65 Rated
- UL Listed
- Uniform and consistent color: ANSI C78.377-2017
- Material: Die Cast Aluminum
- Input line voltage: 120-277V
- Power Factor: >0.9
- Dimmable: 1-10V
- CRI: 70
- ColorTemp: 4000K, 5000K
- Operating temperature: -4°F - 113°F
- Finish Color: Bronze
- 15-30 foot height performance
- Rated 50,000 hours average life

ACCESSORIES

-  Photocell Sensor
-  Emergency Drivers

SAMPLE NUMBER LED-FXCWP40/40K/BZ

STYLE	FAMILY	SERIES	WATTAGE	COLOR TEMP	FINISH COLOR
LED led lighting	FX fixture	CWP cutoff wallpack	40 40 watt	40K 4000K	BZ Bronze



CUT-OFF WALL PACK

WALL & AREA LUMINAIRES

ORDERING

*P= Premium DLC / *S = Standard DLC

Watts (W)	Ordering Code	Description	CCT (K)	Lumens (Lm)	Size	Equiv. Wattage (W)	Dim (V)	IP65 Rated	DLC (S/P)
40	9319	LED-FXCWP40/40K/BZ	4000K	4,861	14.2" x 9.25"	250	1-10V	•	P
40	9320	LED-FXCWP40/50K/BZ	5000K	4,743	14.2" x 9.25"	250	1-10V	•	P
61	9208	LED-FXCWP60/40K/BZ	4000K	7,347	14.2" x 9.25"	400	1-10V	•	P
61	9209	LED-FXCWP60/50K/BZ	5000K	7,482	14.2" x 9.25"	400	1-10V	•	P
80	9443	LED-FXCWP80/40K/BZ	4000K	9,908	14.2" x 9.25"	400-575	1-10V	•	P
80	9444	LED-FXCWP80/50K/BZ	5000K	9,974	14.2" x 9.25"	400-575	1-10V	•	P
120	9445	LED-FXCWP120/40K/BZ	4000K	14,667	14.2" x 9.25"	575-750	1-10V	•	P
120	9446	LED-FXCWP120/50K/BZ	5000K	14,529	14.2" x 9.25"	575-750	1-10V	•	P

ACCESSORIES (Ordered Separately)



Emergency Driver
7334 BAEM15-48BC/MV-A
(Emergency Backup Driver 120-277V)



Photocell
P10036 SEN-PHO-BT-MT/MV
(Button Photocell 120-277V)





DIMENSIONS

40W
6.85-lbs

61W
7.05-lbs

80W
7.48-lbs

120W
10.56-lbs







PHOTOMETRICS CHART

40 Watt
DLC Premium

60 Watt
DLC Premium

80 Watt
DLC Premium

120 Watt
DLC Premium



Illuminance at a Distance

Center Beam Fc	Beam Width
56.0 fc	11.1 R 36.1 R
14.2 fc	22.3 R 72.2 R
6.32 fc	33.4 R 108.3 R
3.55 fc	44.4 R 144.5 R
2.27 fc	55.7 R 180.6 R
1.58 fc	66.8 R 216.7 R

Vert. Spread: 96.2°
HORIZ. Spread: 145.0°

Illuminance at a Distance

Center Beam Fc	Beam Width
85.5 fc	11.1 R 33.3 R
21.5 fc	22.2 R 66.6 R
9.55 fc	33.3 R 99.9 R
5.37 fc	44.3 R 133.2 R
3.44 fc	55.4 R 166.5 R
2.39 fc	66.5 R 199.8 R

Vert. Spread: 95.9°
HORIZ. Spread: 145.6°

Illuminance at a Distance

Center Beam Fc	Beam Width
115 fc	11.4 R 44.8 R
28.7 fc	22.7 R 89.6 R
12.7 fc	34.1 R 134.4 R
7.17 fc	45.3 R 173.2 R
4.59 fc	56.8 R 224.0 R
3.18 fc	68.2 R 264.8 R

Vert. Spread: 97.2°
HORIZ. Spread: 151.4°

Illuminance at a Distance

Center Beam Fc	Beam Width
168 fc	11.3 R 41.4 R
42.1 fc	22.6 R 82.7 R
18.7 fc	33.9 R 124.3 R
10.5 fc	45.1 R 165.5 R
6.73 fc	56.4 R 206.8 R
4.68 fc	67.7 R 248.2 R

Vert. Spread: 96.9°
HORIZ. Spread: 152.6°

PACKAGE

Case Qty 1 pc

