



Item#: **55534**
LED 2' LINEAR HIGH BAY
 HIGH-BAY LUMINAIRES FOR COMMERCIAL AND INDUSTRIAL BUILDINGS

FEATURES

- High lumen output - bright and high lumen per watt.
- Integrated LED - maintenance free.
- Replaces HID and fluorescent fixtures.
- Wide beam angle - uniform light distribution.
- All steel surfaces are painted after fabrication for smooth edges and rounded corners.

MOUNTING

Designed for suspended or pendent mounting.

APPLICATION

Larger warehouses, retail applications, commercial buildings and work areas.

PERFORMANCE DATA

ELECTRICAL

Wattage	128W
Voltage	120-277V
Current	1.06A
Power Factor	0.9
Total Harmonic Distortion (THD)	--

LIGHTING PERFORMANCE

Lumens	20480
Lumens Per Watt (LPW)	160
Color Temperature (CCT)	4000K
Color Rendering (CRI)	80
R9 (Red Value)	--
R13 (Skin Tones)	--
Beam Angle	120°
Light Distribution	--
BUG Rating (Backlight, Uplight, and Glare)	--
Dimmable Lighting Control	<i>Dimmable</i> 0-10V, Range 10% - 100%

ENVIRONMENT

Operating Temperature	-4° ~ 122°F
Suitable Location	DAMP
Ingress Protection Rating	IP40

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	5

COMPONENTS

LED Light Source	--
Driver	--

CONSTRUCTION

Housing	24 Gauge C.R.S.
Lens	Acrylic (PMMA)
Base / Power Supply	Hard Wired
Finish	White

QUALIFICATIONS

Pending

Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.

Item#: **55534**
LED 2' LINEAR HIGH BAY




DIMENSIONS (Inches)

Length	24.8"
Width	15"
Height	2.2"
Net Weight (Lbs)	10.4
Chain Length	41.3" (2 ea.)

SUPPORTING DOCUMENTS (Grey = not available at this time.)

Product Sheet	VIEW
Install Instructions	VIEW
IES Download from Web Item	VIEW
LM79	VIEW
LM80	VIEW



ITEM INFORMATION

PACKAGING

		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	1	811768025422	--	--
Country of Origin	China			
HS Tariff	9405.10.6020			

ORDERING

ITEM#	DESCRIPTION	CASE
55534	LED 2' LINEAR HL HIGH BAY 128W/40K/FR LENS/V-HOOKS & CHAIN/DIMMABLE - SUPERIOR LIFE®	1

ACCESSORIES

55219	PENDENT MOUNT FOR 55222/55223/HL LINEAR HIGH BAY - SUPERIOR LIFE®	25
54896	360° LOW/HIGH BAY FIXTURE OCCUPANCY PIR SENSOR 30' DIA, 8-40' HEIGHT 800W/1200W • 120/277V - SL®	50
54897	360° LOW BAY BI-LEVEL AND DAYLIGHT HARVEST MICROWAVE SENSOR 48' DIA, 8-20' HEIGHT 800W/1200W • 120/277V - SL®	50
54898	360° HIGH BAY BI-LEVEL AND DAYLIGHT HARVEST MICROWAVE SENSOR 60' DIA, 8-50' HEIGHT 800W/1200W • 120/277V - SL®	50
54894	EXTENDER MOUNT FOR SENSOR 54896/54897/54898 - SUPERIOR LIFE®	100
55319	EMERGENCY PACK FOR LED FIXTURE 8W/90 MIN/INTEGRATION TYPE - SL® T20C (For use with drivers that are 100W or less.)	6
55320	EMERGENCY PACK FOR LED FIXTURE 16W/90 MIN/INTEGRATION TYPE - SL® T20C (For use with drivers that are 100W or less.)	6
55321	EMERGENCY PACK FOR LED FIXTURE 25W/90 MIN/INTEGRATION TYPE - SL® T20C (For use with drivers that are 100W or less.)	6
55533	MOUNTING PLATE/INTEGRATED EM PACK FOR HL HIGH BAYS - SUPERIOR LIFE®	100
45002	100' ROLL NO. 12 JACK CHAIN - SUPERIOR LIFE®	Per Foot

REPLACEMENT PARTS

--	REPLACEMENT DRIVER	1
----	--------------------	---

ADDITIONAL INFORMATION:

Family Item(s): 55535/5000K

Note: When using an Emergency Pack with the fixture, cable mounting is recommended to control the balance of the fixture.