







Item#: 55580-8WEM LED 1X4 SPEC-SELECT™ BACK-LIT PANEL

1X4 LUMINARIES FOR AMBIENT LIGHTING OF INTERIOR COMMERCIAL SPACES

FEATURES

Spec-Select™ Panels feature adjustable wattage and color temperature for the perfect balance of light in any application.

- · Energy efficient
- No flickering
- 8W emergency battery pre-installed

APPLICATION

Ideal for retrofitting inefficient fixtures in malls, hospitals, airports, offices, lobbies and other residential and commercial applications.

ELECTRICAL

Wattage	25W / 30W / 40W
Voltage	120-277V
Current	0.33-0.14A
Power Factor	0.9
Total Harmonic Distortion (THD)	10

LIGHTING PERFORMANCE

Lumens	2900-4400
Lumens Per Watt (Lm/W)	110
Color Temperature (CCT)	3500K / 4100K / 5000K
Color Rendering (CRI)	82
R9 (Red Value)	2
R13 (Skin Tones)	81
Beam Angle	120°
Light Distribution	Type VS
BUG Rating (Backlight, Uplight, and Glare)	B2 - U0 - G1
Dimmable Lighting Control	("Dimmable 0-10V, Range 10% - 100%

ENVIRONMENT

Operating Temperature	-4 ~ 113°F
Suitable Location	DAMP
Ingress Protection Rating	IP40

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	5

COMPONENTS

LED Light Source	Runlite 2835
Driver	XZ-SE40B-380105
Emergency Battery	55394

CONSTRUCTION

Housing	Aluminum
Lens	Frosted
Base / Power Supply	Hard Wired
Finish	White

QUALIFICATIONS





Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.

Item#: 55580-8WEM LED 1X4 SPEC-SELECT™ BACK-LIT PANEL






DIMENSIONS (Inches)

Length	47.8"
Width	11.9"
Height	1.6"
Weight (Lbs)	

SUPPORTING DOCUMENTS (Grev = not available at this time.)

3011 Official Docoments (urey = In	ot available at tills tillie.)
Product Sheet	VIEW
Install Instructions	VIEW
Emergency Battery	VIEW
IES Download from Web Item	VIEW
LM79	VIEW
LM80	VIEW



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	2	10811768024828		
Individual Box	1	811768024821	N/A	
Country of Origin	China			
HS Tariff	9405.10.6020			

ORDERING

ITEM#	DESCRIPTION	CASE
55580-8WEM	LED 1X4 SPEC-SELECT™ PANEL - 25/30/40W/35-50K/120-277V/DIMMABLE/8W EM BATTERY - SUPERIOR LIFE® DLC ®	2
ACCESSORIES		
55127	1X4 FLANGE KIT FOR PANEL & TROFFER/WHITE - SUPERIOR LIFE®	1
55530	1X4 SURFACE MOUNTED KIT FOR LED BACK-LIT PANEL/WHITE - SUPERIOR LIFE®	1
55445	SUSPENDED CABLE MOUNTING KIT FOR LED PANEL/V6 - SUPERIOR LIFE®	100
REPLACEMENT I	PARTS	
55394	EMERGENCY PACK FOR LED PANEL 8W/90 MIN - SUPERIOR LIFE®	1
XZ-SE40B-38010	5 REPLACEMENT LED DRIVER	1

ADDITIONAL INFORMATION:

- Default settings; 40W, 5000K.
- When the fixture is in emergency mode the color temperature will default to 5000K.
- The color temperature and wattage may be adjusted by two slide switches integrated into the driver. The color temperature and wattage should be selected prior to installation.

