



Item#: **55594**
LED 4' SPEC-SELECT™
DESIGNER STRIP RETROFIT
 DIRECT LINEAR AMBIENT LUMINARIES

FEATURES

Spec-Select™ Designer Strips Retrofit feature adjustable wattage and color temperature for the perfect balance of light in any application.

- Energy efficient
- No flickering
- Quick and easy retrofit

APPLICATION

Ideal for retrofitting existing strip fixtures. Universal design fits most 4.25" to 5.25" wide T8/T12 fluorescent strip.

COMPLETED RETROFIT
Strip Fixture not included.



PERFORMANCE DATA

ELECTRICAL

Wattage	22W / 30W / 40W
Voltage	120-277V
Current	0.33-0.14A
Power Factor	0.9
Total Harmonic Distortion (THD)	10

LIGHTING PERFORMANCE

Lumens	2992-5280
Lumens Per Watt (Lm/W)	130
Color Temperature (CCT)	3500K / 4100K / 5000K
Color Rendering (CRI)	82
R9 (Red Value)	6
R13 (Skin Tones)	82
Beam Angle	130°
Light Distribution	Very Short, Type II
BUG Rating (Backlight, Uplight, and Glare)	B2 - U3 - G2
Dimmable Lighting Control	<i>Dimmable</i> 0-10V, Range 10% - 100%

ENVIRONMENT

Operating Temperature	-4 ~ 122°F
Suitable Location	DAMP
Ingress Protection Rating	IP40

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	5

COMPONENTS

LED Light Source	Seoul 3528
Driver	SIL60-I900

CONSTRUCTION

Housing	Aluminum
Lens	Frosted
Base / Power Supply	Hard Wired
Finish	White

QUALIFICATIONS



Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.


Item#: **55594**
LED 4' SPEC-SELECT™ DESIGNER STRIP RETROFIT



ITEM INFORMATION

DIMENSIONS (Inches)

Length	48.3"
Width	5.8"
Height	2.4"
Net Weight (Lbs)	5.4



SUPPORTING DOCUMENTS (Grey = not available at this time.)

Product Sheet	VIEW
Install Instructions	VIEW
IES Download from Web Item	VIEW
LM79	VIEW
LM80	VIEW

PACKAGING

		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	2	10811768024507	49.8" x 7.2" x 6.2"	14.1
Individual Box	1	811768024500	--	7.1
Country of Origin	China			
HS Tariff	9405.10.6020			

ORDERING

ITEM#	DESCRIPTION	CASE
55594	LED 4' SPEC-SELECT™ DESIGNER STRIP RETROFIT - 22/30/40W/35-50K/120-277V/DIMMABLE - SUPERIOR LIFE® DLC®	2

ACCESSORIES

54896	360° LOW/HIGH BAY FIXTURE OCCUPANCY PIR SENSOR 30' DIA, 8-40'HEIGHT 800W/1200W • 120/277V - SUPERIOR LIFE®	50
54897	360° LOW BAY BI-LEVEL AND DAYLIGHT HARVEST MICROWAVE SENSOR 48' DIA, 8-20' HEIGHT 800W/1200W • 120/277V - SL®	50
54898	360° HIGH BAY BI-LEVEL AND DAYLIGHT HARVEST MICROWAVE SENSOR 60' DIA, 8-50' HEIGHT 800W/1200W • 120/277V - SL®	50
54894	EXTENDER MOUNT FOR SENSOR 54896/54897/54898 - SUPERIOR LIFE®	100
55390	EMERGENCY PACK FOR LED FIXTURE 8W/90 MIN/SPLIT TYPE/L - SL® T20C (For use with drivers that are 100W or less.)	10
55391	EMERGENCY PACK FOR LED FIXTURE 16W/90 MIN/SPLIT TYPE/L - SL® T20C (For use with drivers that are 100W or less.)	10
55392	EMERGENCY PACK FOR LED FIXTURE 25W/90 MIN - SPLIT TYPE/L - SL® T20C (For use with drivers that are 100W or less.)	10

REPLACEMENT PARTS

555948	REPLACEMENT LENS FOR 4' SPEC-SELECT™ DESIGNER STRIP RETROFIT	1
SIL60-I900	REPLACEMENT DIMMABLE LED DRIVER	1

ADDITIONAL INFORMATION:

- Default settings; 40W, 5000K.
- The color temperature and wattage may be adjusted by two slide switches integrated into the driver box. The color temperature and wattage should be selected prior to installation.

