



Item#: **55615**
LED 4' SPEC-SELECT™
ARCHITECTURAL DESIGNER STRIP
DIRECT LINEAR AMBIENT LUMINARIES

FEATURES

Spec-Select™ Architectural Designer Strips feature adjustable wattage and color temperature for the perfect balance of light in any application.

- Energy efficient
- No flickering

APPLICATION

Ideal for larger warehouses, retail applications, commercial buildings and work areas.

ELECTRICAL

| | |
|---------------------------------|-----------------|
| Wattage | 34W / 38W / 45W |
| Voltage | 120-277V |
| Current | 0.375A |
| Power Factor | 0.9 |
| Total Harmonic Distortion (THD) | 10 |

LIGHTING PERFORMANCE

| | |
|--|--|
| Lumens | 4420-5850 |
| Lumens Per Watt (Lm/W) | 130 |
| Color Temperature (CCT) | 3500K / 4100K / 5000K |
| Color Rendering (CRI) | 82 |
| R9 (Red Value) | -- |
| R13 (Skin Tones) | -- |
| Beam Angle | 130° |
| Light Distribution | -- |
| BUG Rating (Backlight, Uplight, and Glare) | -- |
| Dimmable Lighting Control | <i>Dimmable</i> 0-10V, Range 10% - 100% |

ENVIRONMENT

| | |
|---------------------------|-------------|
| Operating Temperature | -4 ~ 122°F |
| Suitable Location | DAMP |
| Ingress Protection Rating | IP40 |

LIFESPAN

| | |
|----------------------|----------|
| Average Life (Hours) | 50,000 |
| Warranty (Years) | 5 |

COMPONENTS

| | |
|------------------|----|
| LED Light Source | -- |
| Driver | -- |

CONSTRUCTION

| | |
|---------------------|------------|
| Housing | Aluminum |
| Lens | Frosted |
| Base / Power Supply | Hard Wired |
| Finish | White |

QUALIFICATIONS

Pending



Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.

Item#: **55615**
LED 4' SPEC-SELECT™ ARCHITECTURAL DESIGNER STRIP



DIMENSIONS (Inches)

| | |
|------------------|-------|
| Length | 47.3" |
| Width | 3.4" |
| Height | 3.6" |
| Net Weight (Lbs) | 4.5 |



SUPPORTING DOCUMENTS (Grey = not available at this time.)

| | |
|----------------------------|------|
| Product Sheet | VIEW |
| Install Instructions | VIEW |
| IES Download from Web Item | VIEW |
| LM79 | VIEW |
| LM80 | VIEW |

PACKAGING

| | | UPC | DIMENSIONS (LxWxH) | GROSS WEIGHT (Lbs) |
|-------------------|--------------|----------------|----------------------|--------------------|
| Master Carton | 6 | 10811768022909 | 49.6" x 11.7" x 8.4" | 37.9 |
| Individual Box | 1 | 811768022902 | -- | 6.3 |
| Country of Origin | China | | | |
| HS Tariff | 9405.10.6020 | | | |

ORDERING

| ITEM# | DESCRIPTION | CASE |
|-------|--|------|
| 55615 | LED 4' SPEC-SELECT™ ARCHITECTURAL DESIGNER STRIP - 34/38/45W/35-50K/120-277V/DIMMABLE - SUPERIOR LIFE® | 6 |

ACCESSORIES

| | | |
|-------|--|-----|
| 54896 | 360° LOW/HIGH BAY FIXTURE OCCUPANCY PIR SENSOR 30" DIA, 8-40' HEIGHT 800W/1200W • 120/277V - SUPERIOR LIFE® | 50 |
| 54897 | 360° LOW BAY BI-LEVEL AND DAYLIGHT HARVEST MICROWAVE SENSOR 48" DIA, 8-20' HEIGHT 800W/1200W • 120/277V - SL® | 50 |
| 54898 | 360° HIGH BAY BI-LEVEL AND DAYLIGHT HARVEST MICROWAVE SENSOR 60" DIA, 8-50' HEIGHT 800W/1200W • 120/277V - SL® | 50 |
| 54894 | EXTENDER MOUNT FOR SENSOR 54896/54897/54898 - SUPERIOR LIFE® | 100 |
| 55456 | ROW ALIGNER FOR DESIGNER STRIP/V2 - SUPERIOR LIFE® | 100 |
| 55390 | EMERGENCY PACK FOR LED FIXTURE 8W/90 MIN/SPLIT TYPE/L - SL® T20C (For use with drivers that are 100W or less.) | 1 |
| 55391 | EMERGENCY PACK FOR LED FIXTURE 16W/90 MIN/SPLIT TYPE/L - SL® T20C (For use with drivers that are 100W or less.) | 1 |
| 55392 | EMERGENCY PACK FOR LED FIXTURE 25W/90 MIN - SPLIT TYPE/L - SL® T20C (For use with drivers that are 100W or less.) | 1 |

REPLACEMENT PARTS

| | | |
|----|---------------------------------|---|
| -- | REPLACEMENT DIMMABLE LED DRIVER | 1 |
|----|---------------------------------|---|

ADDITIONAL INFORMATION:

- Default settings; 45W, 5000K.
- The color temperature and wattage may be adjusted by two slide switches integrated on the side of the fixture. The color temperature and wattage should be selected prior to installation.

