



Item#: **55616**
LED 8' SPEC-SELECT™
ARCHITECTURAL DESIGNER STRIP
DIRECT LINEAR AMBIENT LUMINARIES

FEATURES

Spec-Select™ Architectural Designer Strips feature adjustable wattage and color temperature for the perfect balance of light in any application.

- Energy efficient
- No flickering

APPLICATION

Ideal for larger warehouses, retail applications, commercial buildings and work areas.

ELECTRICAL

Wattage	65W / 75W / 90W
Voltage	120-277V
Current	0.75A
Power Factor	0.9
Total Harmonic Distortion (THD)	10

LIGHTING PERFORMANCE

Lumens	8450-11700
Lumens Per Watt (Lm/W)	130
Color Temperature (CCT)	3500K / 4100K / 5000K
Color Rendering (CRI)	82
R9 (Red Value)	--
R13 (Skin Tones)	--
Beam Angle	130°
Light Distribution	--
BUG Rating (Backlight, Uplight, and Glare)	--
Dimmable Lighting Control	<i>Dimmable</i> 0-10V, Range 10% - 100%

ENVIRONMENT

Operating Temperature	-4 ~ 122°F
Suitable Location	DAMP
Ingress Protection Rating	IP40

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	5

COMPONENTS

LED Light Source	--
Driver	--

CONSTRUCTION

Housing	Aluminum
Lens	Frosted
Base / Power Supply	Hard Wired
Finish	White

QUALIFICATIONS

Pending



Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.

Item#: **55616**
LED 8' SPEC-SELECT™ ARCHITECTURAL DESIGNER STRIP



DIMENSIONS (Inches)

Length	94.2"
Width	3.4"
Height	3.6"
Net Weight (Lbs)	9



SUPPORTING DOCUMENTS (Grey = not available at this time.)

Product Sheet	VIEW
Install Instructions	VIEW
IES Download from Web Item	VIEW
LM79	VIEW
LM80	VIEW

PACKAGING

		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	4	10811768022640	96.7" x 8.5" x 7.5"	44.3
Individual Box	1	811768022643	--	11.1
Country of Origin	China			
HS Tariff	9405.10.6020			

ORDERING

ITEM#	DESCRIPTION	CASE
55616	LED 8' SPEC-SELECT™ ARCHITECTURAL DESIGNER STRIP - 65/75/90W/35-50K/120-277V/DIMMABLE - SUPERIOR LIFE®	4

ACCESSORIES

54896	360° LOW/HIGH BAY FIXTURE OCCUPANCY PIR SENSOR 30" DIA, 8-40' HEIGHT 800W/1200W • 120/277V - SUPERIOR LIFE®	50
54897	360° LOW BAY BI-LEVEL AND DAYLIGHT HARVEST MICROWAVE SENSOR 48" DIA, 8-20' HEIGHT 800W/1200W • 120/277V - SL®	50
54898	360° HIGH BAY BI-LEVEL AND DAYLIGHT HARVEST MICROWAVE SENSOR 60" DIA, 8-50' HEIGHT 800W/1200W • 120/277V - SL®	50
54894	EXTENDER MOUNT FOR SENSOR 54896/54897/54898 - SUPERIOR LIFE®	100
55456	ROW ALIGNER FOR DESIGNER STRIP/V2 - SUPERIOR LIFE®	100
55390	EMERGENCY PACK FOR LED FIXTURE 8W/90 MIN/SPLIT TYPE/L - SL® T20C (For use with drivers that are 100W or less.)	1
55391	EMERGENCY PACK FOR LED FIXTURE 16W/90 MIN/SPLIT TYPE/L - SL® T20C (For use with drivers that are 100W or less.)	1
55392	EMERGENCY PACK FOR LED FIXTURE 25W/90 MIN - SPLIT TYPE/L - SL® T20C (For use with drivers that are 100W or less.)	1

REPLACEMENT PARTS

--	REPLACEMENT DIMMABLE LED DRIVER	1
----	---------------------------------	---

ADDITIONAL INFORMATION:

- Default settings; 90W, 5000K.
- The color temperature and wattage may be adjusted by two slide switches integrated on the side of the fixture. The color temperature and wattage should be selected prior to installation.

