





Item#: **55705 LED 6W ADD-ON EMERGENCY KIT**

FOR LED INDOOR FIXTURES

FEATURES

- Kit includes; an LED emergency driver, battery, high efficacy LED module and test light indicator.
- Easy Installation
- Uncomplicated Does not require you to splice into existing fixture driver wiring like other EM backups.
- Standalone system Has its own LED light source, doesn't try to operate the fixture LED which can have compatibility or brightness issues.

APPLICATION

Provides emergency lighting solutions for a wide variety of fixtures

OUTPUT

Output Power	6W Max.
Output Voltage	6-8.4 Vdc

INPUT

Input Power	5W Max.
Input Current	100mA Max.
Input Voltage	100-277V • 50/60Hz

PERFORMANCE

Lumens	760
Lumens Per Watt (Lm/W)	127
Color Temperature	5000K
Emergency Time	90 Min.
Recharge Time Required	24 Hours Max.
Battery Type	Lithium-Ion

ENVIRONMENT

Operating Temperature	32° ~ 122°F
Suitable Location	DAMP
Ingress Protection Rating	IP20

LIFESPAN

Warranty (Years)	2
------------------	---

QUALIFICATIONS




Published lumens on LED products are approximate and may vary slightly. - Specifications are subject to change without notice.

Item#: **55705 LED 6W EMERGENCY KIT**






DIMENSIONS (Inches)	DRIVER	BATTERY	MODULE
Length	5.9"	3"	3.5"
Width	1.7"	1.6"	0.83"
Height	0.87"	1.2"	
Weight (Lbs)			



LED MODULE 3.5"



SUPPORTING DOCUMENTS (Grey = not available at this time.)

Product Sheet	VIEW
Install Instructions	VIEW

PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	20	10811768025382	16.3" x 10.2" x 7.7"	16.5
Individual Box	1	811768025385	9.7" x 3.9" x 1.4"	0.83
Country of Origin	China			
HS Tariff				

0.83"

ORDERING

ITEM#	DESCRIPTION	CASE
55705	EMERGENCY KIT FOR LED FIXTURE 6W/5000K//90 MIN/100-277V - SUPERIOR LIFE®	20

ADDITIONAL INFORMATION:

- An un-switched AC power source is required.
- This device is designed for use in fixtures listed for dry and damp locations.