





Item#: 83691 **OUTDOOR NON-CUTOFF AND SEMI-CUTOFF WALL-MOUNTED AREA LUMINAIRES** 

# **FEATURES**

- Easy installation
- Replaces 50W HID
- Sealed housing for outdoor applications
- · Polycarbonate optical lens
- · With Photo Cell

### **APPLICATION**

Ideal for security, pathway and perimeter lighting, building entry ways and walkways.

# **ELECTRICAL**

Wattage	23W
Voltage	120-277V
Current	0.23A
Power Factor	0.9
Total Harmonic Distortion (THD)	13.2
LIGHTING PERFORMANCE	

Lumens	3174		
Lumens Per Watt (Lm/W)	136		
Color Temperature (CCT)	4000K		
Color Rendering (CRI)	73		
R9 (Red Value)	-34		
R13 (Skin Tones)			
Beam Angle	90°		
Light Distribution	Very Short, Type IV		
BUG Rating (Backlight, Uplight, and Glare)	B1 - U3 - G2		
Dimmable Lighting Control	<b>(Dimmable</b> 0-10V, Range 10% - 100%		

### **ENVIRONMENT**

Operating Temperature	-22° ~ 113°F
Suitable Location	WET
Ingress Protection Rating	IP65

# **LIFESPAN**

Average Life (Hours)	50,000
Warranty (Years)	5

### **COMPONENTS**

LED Light Source	Luxeon 3030 2D
Driver	WP-HLA-030U

# **CONSTRUCTION**

Housing	Aluminum Alloy / PC	
Lens	Clear	
Base / Power Supply	Hard Wired	
Finish	Black	

# **QUALIFICATIONS**

Model Number	MWP-25-[D,P]-40K
--------------	------------------





Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.

# Item#: 83691 LED MINI WALL PACK






# **DIMENSIONS** (Inches)

Length	8.3"
Width	5.5"
Height	3.5"
Net Weight (Lbs)	

### **SUPPORTING DOCUMENTS** (Grey = not available at this time.)

Corr String Documents (arey - not available at this time.)		
Product Sheet	VIEW	
Install Instructions	VIEW	
IES Download from Web Item	VIEW	
LM79	VIEW	
LM80	VIEW	



PACKAGING		UPC	<b>DIMENSIONS</b> (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	8	10811768022978	5.6" x 3.9" x 8.5"	16.3
Individual Box	1	811768022971		2
Country of Origin	China			
HS Tariff				

### **ORDERING** Qualification Model # MWP-25-[D,P]-40K

ITEM#	DESCRIPTION	CASE
83691	LED MINI WALL PACK 25W/40K/CLEAR/BLACK/PHOTO CELL/120-277V/DIMMABLE - SUPERIOR LIFE® <b>DLC</b> ®	8
REPLACEMENT PARTS		
WP-HLA-030U	REPLACEMENT DRIVER FOR MINI WALL PACK	1

# **ADDITIONAL INFORMATION:**

Family Item(s): 83689 without Photo Cell

**Note:** To prevent water damage which may shorten the life of an exterior mounted fixture; the fixture should be properly weather sealed according to the installation instructions or between the fixture base and mounting surface. Damage due to improper installation may void the warranty.