



OUTDOOR POLE/ARM-MOUNTED AREA AND ROADWAY LUMINAIRES - ARCHITECTURAL FLOOD AND SPOT LUMINAIRES

FEATURES

- Elegant and modern appearance
- Housing coated with corrosion resistant polyester powder
- Multi-faceted optic design to distribute light evenly and reduce glare
- Advanced technology, no electrical interference.
- 240° adjustable angle
- Surge protection device

- APPLICATION

Arenas, sports fields, plazas, airports, courtyards and public areas.





ELECTRICAL

Wattage	299W
Voltage	277-480V
Power Factor	0.9
Total Harmonic Distortion (THD)	8.8
LIGHTING PERFORMANCE	

Lumens	48841
Lumens Per Watt (Lm/W)	163
Color Temperature (CCT)	5000K
Color Rendering (CRI)	73
R9 (Red Value)	-25
Beam Angle	30°
Light Distribution	Type VS
BUG Rating (Backlight, Uplight, and Glare)	B5 - U4 - G1
Dimmable Lighting Control	(Dimmable 0-10V, Range 10% - 100%

ENVIRONMENT

Operating Temperature	-22° ~ 122°F
Suitable Location	WET
Ingress Protection Rating	IP66

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	5

COMPONENTS

LED Light Source	Luxeon 5050
Driver	ESD-320S620DT

CONSTRUCTION

Housing	Die-Cast Aluminum	
Lens	PC	
Base / Power Supply	Hard Wired	
Finish	Black	
Effective Projected Area (EPA)	1.59 ft ²	
Wind Shear Rating	116.3 mph	

QUALIFICATIONS

Model Number RSTL-300-D-EV-50K







Visit www.designlights.org/search to confirm qualification. - Published lumens on LED products are approximate and may vary slightly. - Specifications are subject to change without notice.

Item#: **84246**LED STADIUM LIGHT






DIMENSIONS (Inches)

Length	16.3"
Width/Diameter	15.9"
Height	19.7"
Net Weight (Lbs)	27.6

SUPPORTING DOCUMENTS (Grey = not available at this time.)

	- ()
Product Sheet	VIEW
Install Instructions	VIEW
IES Download from Web Item	VIEW
LM79	VIEW
LM80	VIEW



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	1	811768026542	17.7" x 17.7" x 14"	32
Country of Origin	China			
HS Tariff	9405.10.6020			

ORDERING * Qualification Model # RSTL-300-D-EV-50K

ITEM#	DESCRIPTION	CASE
84246	LED 300W STADIUM/50K/30°/277-480V/DIMMABLE/V2 - SUPERIOR LIFE® DLC ®	1
ACCESSORIES		
84080	U BRACKET AND SLIP FITTER FOR 300W-600W STADIUM LIGHT - SUPERIOR LIFE®	5
84205	LASER SCOPE KIT FOR LED STADIUM LIGHT - SUPERIOR LIFE®	12
REPLACEMENT	PARTS	
ESD-320S620DT	320W REPLACEMENT LED DRIVER	1

ADDITIONAL INFORMATION:

Item may be special order; please consult with P.Q.L.