





Item#: 85001
LED SIGN - DIRECT WIRE LINEAR T8
INTERNAL DRIVER LAMP-STYLE RETROFIT KITS
(UL TYPE B)

FEATURES - SINGLE ENDED DIRECT WIRE

- Top of the line retrofit for standard fluorescent lamps
- Back-to-Back LED Strips for illuminating 2-sided signs
- · No ballast required, lamp runs off main
- Exceptional efficacy
- · End cap rotates 90° for precise positioning
- Multi-use end cap design can be used with both HO and Medium Bi Pin sockets.

*Non-shunted sockets required, see install instructions for further details. Not for use with emergency fixtures.

		07		0.5	•
ы	-	-	K	11 - 11	

Wattage	15W
Voltage	120-277V
Current	140mA
Power Factor	0.9
Total Harmonic Distortion (THD)	<25

LIGHTING PERFORMANCE

2100
162
6500K
83
330°
Sur TOMMARL D

ENVIRONMENT

Operating Temperature	-4° ~ 104°F	
Suitable Location	DAMP	
Ingress Protection Rating	IP20	
Suitable Fixture Type	Enclosed	

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	3

COMPONENTS

LED Light Source	Samsung 1228
------------------	--------------

CONSTRUCTION

Housing	Nano Plastic / Aluminum Plastic End Caps	
Lens	Clear	
Base / Power Supply	G13 - Medium Bi Pin / R17D	

QUALIFICATIONS



Published lumens on LED products are approximate and may vary slightly. - Specifications are subject to change without notice.

Item#: **85001 LED SIGN - DIRECT WIRE LINEAR T8**






DIMENSIONS (Inches)

Length (MOL)	39.8"	
Width/Diameter (MOD)	1	
Net Weight (Lbs)		

SUPPORTING DOCUMENTS (Grev = not available at this time.)

Correction and Document (arey - not available at this time.)		
Product Sheet	VIEW	
Install Instructions	VIEW	
IES Download from Web Item	VIEW	
LM79	VIEW	
LM80	VIEW	



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	10	10811768022947	42.1" x 7.9" x 4.9"	6.6
Individual Box	1	811768022940		0.66
Country of Origin	China			
HS Tariff				

ORDERING

ITEM#	DESCRIPTION	CASE
85001	LED SIGN 42" 15WT8/65K/CL/H0/120-277V - SUPERIOR LIFE°	10