



Item#: **91488**
LED DUAL POWER LINEAR T8
INTERNAL DRIVER LAMP-STYLE RETROFIT KITS
(UL TYPE B)

FEATURES

Our T8 LED tube lamp provides exceptional LED lighting with reduced energy and maintenance costs. The linear LED does not use a fluorescent ballast to work; instead they feature a built-in universal line voltage driver, making it a top of the line replacement for standard fluorescent lamps.


DOUBLE ENDED DIRECT WIRE

- No ballast required, lamp runs off main
- Exceptional efficacy
- Suitable for both Shunted and Non-Shunted Sockets

ELECTRICAL

Wattage	14W
Voltage	120-277V
Current	125mA
Power Factor	0.9
Total Harmonic Distortion (THD)	20

LIGHTING PERFORMANCE

Lumens	1800
Lumens Per Watt (Lm/W)	129
Color Temperature (CCT)	5000K
Color Rendering (CRI)	82
R9 (Red Value)	9.3
R13 (Skin Tones)	83.9
Beam Angle	210°
Light Distribution	Type VS
BUG Rating (Backlight, Uplight, and Glare)	B1 - U1 - G1
Dimmable Lighting Control	

ENVIRONMENT

Operating Temperature	-4 ~ 114°F
Suitable Location	DAMP
Ingress Protection Rating	IP20
Suitable Fixture Type	Enclosed

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	5

COMPONENTS

LED Light Source	Toyoda 2835
------------------	-------------

CONSTRUCTION

Housing	Glass / Plastic End Caps
Lens	Frosted / Safety Coated
Base / Power Supply	G13 - Medium Bi Pin

QUALIFICATIONS



Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.

Item#: **91488**
LED DUAL POWER LINEAR T8




DIMENSIONS (Inches)

Length (MOL)	47.8"
Width/Diameter (MOD)	1"
Weight (Lbs)	--

SUPPORTING DOCUMENTS (Grey = not available at this time.)

Product Sheet	VIEW
Install Instructions	VIEW
IES Download from Web Item	VIEW
LM79	VIEW
LM80	VIEW



PACKAGING

		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	25	10811768028369	48.8" x 5.9" x 5.9"	14.8
Individual Box	1	811768028362	--	0.59
Country of Origin	China			
HS Tariff	8539.50.0050			

ORDERING

ITEM#	DESCRIPTION	CASE
91488	LED 4' 14WT8/50K/FR/DUAL POWER/SAFETY COATED/V6 - SUPERIOR LIFE® DLC®	25

ACCESSORIES

90405	LED 5W/90 MIN. EMERGENCY BATTERY BACKUP FOR (1) T8 DIRECT WIRE LAMP/120-277V - SUPERIOR LIFE® T20C	25
-------	--	----

ADDITIONAL INFORMATION:

Family Item(s): 91487/4000K

- PQL Direct-Wire (UL Type B) Lamps are designed for use with PQL LED-Ready fixtures (follow lamp wiring instructions). When using any alternate-brand fixture, please review the specific PQL lamp installation guide wiring requirements first, to make sure the fixture is compatible before lamp installation.