



Item#: **91492**
LED DUAL POWER LINEAR T8
 INTERNAL DRIVER LAMP-STYLE RETROFIT KITS
 (UL TYPE B)

FEATURES

Our T8 LED tube lamp provides exceptional LED lighting with reduced energy and maintenance costs. The linear LED does not use a fluorescent ballast to work; instead they feature a built-in universal line voltage driver, making it a top of the line replacement for standard fluorescent lamps.

DOUBLE ENDED DIRECT WIRE

- No ballast required, lamp runs off main
- Thermal fuse - for added safety
- Wide beam design
- Exceptional efficacy
- Suitable for both Shunted and Non-Shunted Sockets



ELECTRICAL

Wattage	18.5W
Voltage	120-277V
Current	167mA
Power Factor	0.9
Total Harmonic Distortion (THD)	20

LIGHTING PERFORMANCE

Lumens	2450
Lumens Per Watt (Lm/W)	132
Color Temperature (CCT)	3500K
Color Rendering (CRI)	82
R9 (Red Value)	N/A
R13 (Skin Tones)	N/A
Beam Angle	210°
Light Distribution	Type VS
BUG Rating (Backlight, Uplight, and Glare)	B2 - U1 - G1
Dimmable Lighting Control	

ENVIRONMENT

Operating Temperature	-4 ~ 113°F
Suitable Location	DAMP
Ingress Protection Rating	IP20
Suitable Fixture Type	Enclosed

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	5

COMPONENTS

LED Light Source	Bridgelux
------------------	-----------

CONSTRUCTION

Housing	Glass / Plastic End Caps
Lens	Frosted
Base / Power Supply	G13 - Medium Bi Pin

QUALIFICATIONS



Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.

Item#: **91492**
LED DUAL POWER LINEAR T8




DIMENSIONS (Inches)

Length (MOL)	47.8"
Width/Diameter (MOD)	1"
Weight (Lbs)	--

SUPPORTING DOCUMENTS (Grey = not available at this time.)

Product Sheet	VIEW
Install Instructions	VIEW
IES Download from Web Item	VIEW
LM79	VIEW
LM80	VIEW



PACKAGING

		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	25	10811768021285	48.8" x 5.9" x 5.9"	14.4
Individual Box	1	811768021288	--	0.58
Country of Origin	China			
HS Tariff	8539.50.0050			

ORDERING

ITEM#	DESCRIPTION	CASE
91492	LED 4' 18.5WT8/35K/FR/DUAL POWER/V6 - SUPERIOR LIFE® DLC®	25

ACCESSORIES

90405	LED 5W/90 MIN. EMERGENCY BATTERY BACKUP FOR (1) T8 DIRECT WIRE LAMP/120-277V - SUPERIOR LIFE® T20C	25
-------	--	----

ADDITIONAL INFORMATION:

Family Item(s): 91493/4000K • 91447/5000K

- PQL Direct-Wire (UL Type B) Lamps are designed for use with PQL LED-Ready fixtures (follow lamp wiring instructions). When using any alternate-brand fixture, please review the specific PQL lamp installation guide wiring requirements first, to make sure the fixture is compatible before lamp installation.