
# **FDI SERIES**

## FLOOR DROP-IN HEATER



### **IDEAL SPACES**

- Bedrooms
- Living/Family Rooms
- Offices
- Lobbies

#### **COLORS**

Sandal Wood

#### **DIMENSIONS**

- GRILLE | 15-3/8" L x 8-3/4" W
- BACK BOX | 14" L x 7-1/4" W x 6-5/8" D

#### **TEMP RANGE**

■ 55°-90°F

- Conference Rooms
- Hallways
- Waiting Rooms



- Universal size combined with a heavy-duty grille
- Quick Installation mounts between floor joists parallel or perpendicular
- Overheat thermal protector
- Flow pattern is 5 ft. wide and 4 ft. high
- Push-on tab wire terminals
- Quiet operation

MODELS & SPECIFICATIONS						
CATALOG NO.	UPC	VOLTS	CFM	WATTS	AMPS	SHIP WT. (LBS.)
FDI1500	6 85360 02626 8	120	80	1500/750	12.5/6.3	10
FDI1504	6 85360 02628 2	240	80	1500/750	6.3/3.1	10
		208	80	1125/563	5.4/2.7	
FDITSP	6 85360 02619 0	120-240V T'stat Kit				1

NOTE: \*60 hz. single-phase. Do not install in bathroom or other areas where water may enter heater unit. Do not locate where air flow may be obstructed (under drapes, behind doors, etc.). Keep short side 36 in. min. and long side 3 in. min. from side walls. Do not install in ceiling or wall.



