

# INSTALLATION INSTRUCTION

## Flush Mount



### WARNING


IMPORTANT: NEVER attempt any work without shutting off the electricity.

- Read all instructions before installing.
- System is intended for installation by a qualified electrician in accordance with the National Electrical Code and local regulations.
- Go to the main fuse box, or circuit breaker. Place the main power switch in the "OFF" position and unscrew the fuse(s) or switch "OFF" the circuit breaker switch(es) that control the power to the fixture or room that you are working on.
- Place the wall switch in the "OFF" position.

### CAUTION

- All parts must be used as indicated in these instructions. Do not substitute any parts, leave parts out, or use any parts that are worn out or broken. Failure to follow this instruction could invalidate the CSA listing of this fixture.
- CAUTION When handling the fixture, do not apply pressure to the LEDs. Hold the fixture by the base only.

FIG 1



### HARDWARE

- A1** Wire Connector Qty: 3
- B1** Junction Box Screw Qty: 2 + 2 Extra
- O1** Wood Screw & Plastic anchor Qty: 2 Qty: 2
- D1** Mounting bracket Qty: 1

### PREPARATION

1. Shut off the power at the circuit breaker and remove existing fixture, including the mounting hardware.
2. Carefully unpack your new fixture and lay out all the parts on a clear area. Be careful not to lose any small parts necessary for installation.

### CONNECTING THE WIRES (Fig. 2)

3. Connect the fixture input wires to junction box wires as shown in **Fig. 2**, making sure that all wire connectors (A1) are secured. If your outlet box has a ground wire (I1) (Green or bare copper), connect the fixture's ground wire to it. After wires are connected, tuck them carefully inside the junction box.

### MOUNTING THE FIXTURE (Fig. 1)

4. Secure the mounting bracket (D1) to the junction box (F1) using the J-box screws (B1).
5. Drywall: Drill holes in the wall aligned with the key-hole location in the mounting bracket (D1). Insert the mounting anchors (O1).
6. Align the mounting slots on the back of the fixture with the metal tabs on the mounting bracket (D1)
7. Twist lock the fixture to mounting bracket .

Fig.2 Wiring



Fixture Wires	House Wires
Black or Smooth	Black (Hot)
White or Ribbed	White (Neutral)
Bare wire (Ground)	Green or Bare Copper (Ground)