

7602, 7604, 7606, 7608

120V

Catalog #:		Type
Project:		Date
Prepared by:		

2', 4', 6', & 8' Track



DESCRIPTION

Each track section features an extruded aluminum “I” beam channel where connector and feeds simply push into track sections. The track is compatible with the full range of fixtures and accessories and lengths can be cut-to-length by installer. RP Lighting track is designed as a two wire system. Line Voltage, Low Voltage and LED track heads and pendants are available and can be combined with a four foot section of track and floating feed to make up a pre-packed track kit. Many accessories are available to customize a track system.

DESIGN FEATURES

Construction

- Two 12 gauge solid copper conductors
- Rated 20 amps at 120 volts
- Aluminum channel used as system ground
- One-piece insulator ensures consistent conductor spacing for reliable electrical contact
- Insulating bushings supplied at mounting hole locations to prevent shorts to ground
- Available in black, white, and brushed aluminum

Electrical

- Rated: 20 amps at 120 volts

Installation

- Polarity line provides visual cue to align fixture properly
- Supplied with toggle bolts for surface mounting
- Integral top channel accommodates pendant mounting hardware and wire routing to electrical feed
- Connector and feeds simply push into track sections

Certifications

- cULus Certified
- 1 year limited warranty

Features

- Insulating bushings supplied at mounting hole locations to prevent shorts to ground
- Aluminum channel used as system ground
- Injected molded polycarbonate dead-end w/ set screw
- Polarity line provides visual cue to align fixture properly

ORDERING

Example: 7602WH

Model #	SIZE	FINISH
7602, 7604 7606, 7608		
7602	2' Track	BA : Brushed Aluminum
7604	4' Track	WW : White
7606	6' Track	BK : Black
7608	8' Track	

