8062 120V-277V Universal Voltage

atalog #:	Туре
oject:	
	Date
epared by:	

# 6" Tunable Wattage and Selectable CCT Commercial Downlight



#### DESCRIPTION

The 8062 Tunable Wattage and Selectable CCT Commercial Downlight is a one-piece housing and trim designed for easy installation in a retrofit or new construction non-IC applications. The Open Reflector has a wide distribution from many open commercial spaces. Choose between 3 different wattages for lumen output and 5 different LED color temperatures for the look you want.

#### **DESIGN FEATURES**

#### Construction

- Heavy gauge aluminum reflector allows heat dissipation
- Designed to replace most existing 6-3/8" to 7-1/4" aperture downlights
- Two integral tension spring clips included for installation with or without new construction mounting frame accessory

#### Electrical


- 120-277V AC
- 0-10V Dimming
- 50,000 hours projected LED life
- Tunable Wattage:
- 15W | 1350 lms (delivered)
- 23W | 1800 lms (delivered)
- 30W | 2700 lms (delivered)
- Selectable 5CCT: 27K, 3K, 35K, 4K, 5K
- 80 CRI
- Beam Angle: 65°

### **Reflector Finish**

Clear Haze

#### Installation

 Easy-quick metal connector case included allowing easy and sturdier wire connector



#### Certifications

- cCSAus listed for damp location
- Non-IC rated downlight; IC rated mounting plate accessory available
- LED Light Engine: 5 Year Limited Warranty
- Other Components: 1 Year Limited Warranty

ORDERING GUIDE		UIDE	Example: 8062-3TW-5CCT	
Model #	Wattage		ССТ	
8062	-3TW		-5CCT	
8062	-3TW : Tunable Wattage= 15W, 23W, 30W		-5CCT : Selectable CCT 27K, 3K, 35K,4K, 5K	
Accessories			(sold separately)	
8166H		6" Non-IC New Construction Mounting Plate		
8166HIC	;	6" IC New Construction Mounting Plate		



## TEL: 800.937.6925 | Fax: 800.207.9509 | www.rplighting.com

## 2/6/23 R1

RP LIGHTING · FANS

# **Specification & Ordering**

# **New Construction Mounting Plate Accessory**

(sold separately)

- New construction installations use mounting plate 8166H or 8166HIC
- Heavy gauge bar hangers that include captive nails allow for the housing to be secured to ceilings joist or suspended "T" bar construction are included

