

# RXEL24

120V/277V

Catalog #:		Type
Project:		Date
Prepared by:		

## Low-Profile LED Emergency Combo, Wet Listed



### DESCRIPTION

The RXEL24 LED Emergency Combo features a two-head design with an ABS housing and lamp heads, polycarbonate faceplate and snap-in chevrons.

### DESIGN FEATURES

#### Construction

- ABS flame-resistant enclosure and lamp heads
- Single Polycarbonate faceplate

#### Electrical

- 120/277VAC - 60 Hz
- Operating Temperature: 10°C to 40°C
- (2) Adjustable 3.6V | 1W | 90 lms LED Heads
- 3.6V | 1500 mAh Ni-MH Maintenance-free Battery
- Solid-state transfer circuit
- Battery low voltage disconnect protects from deep discharge
- Test switch and battery charging indicator included
- 24 hour recharge with minimum 90 minimum discharge

#### Installation

- Suitable for wall mounting only
- Universal J-Box mounting pattern on back plate

#### Certifications

- UL924 Listed; meets NFPA70, NFPA101 requirements
- ETL listed for wet location
- LED Lamps: 5 Year Limited Warranty
- Other Components: 1 Year Limited Warranty

### ORDERING GUIDE

Example: RXEL24WR

Model #	Lettering
RXEL24	
RXEL24	WR : Red with white housing WG : Green with white housing

